



Figure similar

MLFB-Ordering data 6SL3121-2TE13-0AA4

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		Ambient conditions	
DC link voltage	DC 510 ... 720 V	Installation altitude (without derating)	1000 m (3281 ft)
Electronics power supply	DC 24 V -15 % / +20 %	Cooling ⁸⁾	External air cooling
Current demand, max.	1.15 A	Cooling air requirement	0.008 m³/s
DC-link current I _d	7.2 A	Ambient temperature	
Output current		During operation	
Rated value I _N	2 x 3.0 A	0 ... 40 °C (32 ... 104 °F)	
Base load current I _H	2 x 2.6 A	Connections	
For S6 duty (40%) I _{S6}	2 x 3.5 A		
I _{max}	2 x 9.0 A	Motor end	
Type rating ²⁾		Version	connector (X1, X2)
Based on I _N	2 x 1.6 kW	PE connection	M5 screw
Based on I _H	2 x 1.4 kW	Shield connecting kit	Integrated connection plug (X1, X2)
Current carrying capacity		Max. motor cable length	
DC link busbars	100 A	Shielded	50 m (164 ft)
24 V busbars ⁴⁾	20 A	Unshielded	75 m (246 ft)
DC link capacitance	220 µF	Standards	
		Compliance with standards	CE, cULus
		Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1

MLFB-Ordering data

6SL3121-2TE13-0AA4



Mechanical data		General tech. specifications	
Line side		Sound pressure level (1m)	60.0 dB
Width	50.00 mm (1.97 in)	Power loss, max. ⁹⁾	0.06 kW
Height	380.00 mm (14.96 in)		
Depth	226.00 mm (8.90 in)		
Degree of protection	IP20 / UL open type		
Type of construction	Booksize		
Net weight	5.8 kg (12.79 lb)		

2) Rated output of a typical standard asynchronous motor at 400 V 3 AC

4) If, when connecting several Line Modules and Motor Modules in series, the current carrying capacity exceeds 20 A, another 24 V DC connection is required using a 24 V terminal adapter (max. connectable cross-section 6 mm2, max. protection 20 A).

8) Power units with intensified air cooling thanks to integrated fan

9) Power loss of the Motor Module with rated power including losses of the 24 V DC electronics power supply