

## Data sheet for Motor Module

Article No. : 6SL3320-1TE35-0AA3

Client order no. :  
Order no. :  
Offer no. :  
Remarks :

Item no. :  
Consignment no. :  
Project :



Figure similar

Rated data	
DC link voltage	DC 510 ... 720 V
Electronics power supply	DC 24 V -15 % / +20 %
Current demand, max.	0.90 A
Current consumption 400V AC	1.80 A
<b>DC-link current</b>	
Rated current I <sub>N</sub> DC	
- Basic/Smart Line Module	588 A
- Active Line Module	529 A
Base-load current I <sub>L</sub> DC	
- Basic/Smart Line Module	573 A
- Active Line Module	515 A
Base-load current I <sub>H</sub> DC	
- Basic/Smart Line Module	523 A
- Active Line Module	470 A
<b>Output current</b>	
Rated value I <sub>N</sub>	
Base-load current I <sub>L</sub> <sup>1)</sup>	
Base load current I <sub>H</sub> <sup>2)</sup>	
For S6 duty (40%) I <sub>S6</sub>	
I <sub>max</sub>	
<b>Type rating <sup>3)</sup></b>	
Based on I <sub>N</sub>	
Based on I <sub>H</sub>	
<b>Pulse frequency</b>	
Rated pulse frequency <sup>4)</sup>	
Pulse frequency, max.	
DC link capacitance	9,600 µF
Output frequency for servo control	0 ... 550 Hz
Output frequency for V/f control	0 ... 550 Hz
Output frequency for vector control	0 ... 550 Hz
Ambient conditions	
Installation altitude (without derating)	2,000 m (6,561.68 ft)
Cooling <sup>5)</sup>	External air cooling
Cooling air requirement	0.36 m³/s (12.710 ft³/s)
<b>Ambient temperature</b>	
During operation	0 ... 40 °C (32 ... 104 °F)

Connections	
<b>Motor end</b>	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm²
<b>DC link</b>	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm²
<b>Braking module</b>	
Version	M6 threaded bolt
<b>PE1 connection</b>	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm²
<b>PE2 connection</b>	
Version	2 x M10 screw
Conductor cross-section	2 x 240 mm²
<b>Max. motor cable length <sup>6)</sup></b>	
Shielded	300 m (984.25 ft)
Unshielded	450 m (1,476.38 ft)
Standards	
Compliance with standards	CE, cULus
Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1
Mechanical data	
<b>Line side</b>	
<b>Dimensions</b>	
Width	326 mm (12.83 in)
Height	1,533 mm (60.35 in)
Depth	545 mm (21.46 in)
Degree of protection	IP20
Type of construction	Chassis
Net weight	136 kg (299.83 lb)
General tech. specifications	
Sound pressure level (1m) + 50 Hz / 60 Hz	69 dB / 73 dB
<b>Power loss, max. <sup>7)</sup></b>	
Power loss (50 Hz 400 V)	4.28 kW
Power loss (60 Hz 460 V)	4.50 kW

<sup>1)</sup> The base-load current I<sub>L</sub> is the basis for a duty cycle of 110% for 60 s or 150% for 10 s with a duty cycle duration of 300 s.

<sup>2)</sup> The base load current I<sub>H</sub> is based on a duty cycle of 150% for 60 s or 160% for 10 s with a duty cycle duration of 300 s.

<sup>3)</sup> Rated power of a typ. 6-pole standard induction motor based on I<sub>L</sub> or I<sub>H</sub> at 3 AC 50 Hz 400 V or 3 AC 60 Hz 460 V.

<sup>4)</sup> Information on the correlation between pulse frequency and maximum output current/output frequency is provided in the SINAMICS Low Voltage Configuration Manual.

<sup>5)</sup> Power units with intensified air cooling thanks to integrated fan

<sup>6)</sup> Sum of all motor cables and DC link. Longer cable lengths on request, depending on configuration. More information can be found in the SINAMICS Low Voltage Configuration Manual.

<sup>7)</sup> The specified power loss represents the maximum value at 100% utilization. The value is lower under normal operating conditions.