



Figure similar

Data sheet for Basic Line Modules

Article No. : 6SL3330-1TE34-2AA3

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data	
Line voltage	3 AC 380 ... 480 V
Rated power	
for I _{N DC} (50 Hz 400 V)	200 kW
for I _{H DC} (50 Hz 400 V)	160 kW
for I _{N DC} (60 Hz 460 V)	305 hp
for I _{H DC} (60 Hz 460 V)	245 hp
DC-link current	
Rated current I _{N DC}	420 A
Base-load current I _{H DC} ¹⁾	328 A
Maximum current I _{max DC}	630 A
Input current	
Rated current I _{N E}	364 A
Maximum current I _{max E}	547 A
Maximum precharging current (max. 3 s)	internal
Current drawn	
24 V DC auxiliary power supply	1.1 A
DC link capacitance	
Basic Line Module	7,200 µF
Drive line-up, max.	57,600 µF
Power loss, max. ³⁾	
at 50 Hz 400 V	1.9 kW
at 60 Hz 460 V	1.9 kW

Connections	
Line connection U1, V1, W1	
Design	2 x Flat connector for M10 screw
Conductor cross-section, max. (IEC)	2 x 240 mm ²
DC link connection DCP, DCN	
Design	2 x M10 screw
Conductor cross-section, max. (IEC)	2 x 240 mm ²
PE/GND connection	
Design	2 x 2 x hole for M10
Conductor cross-section, max. (IEC)	2 x 240 mm ²
Mechanical data	
Degree of protection	IP00
Frame size	FB
Net weight	96 kg (211.64 lb)
Dimensions	
Width	310 mm (12.2 in)
Height	1,164 mm (45.83 in)
Depth	352 mm (13.86 in)
Other technical specifications	
Cooling air requirement	0.17 m ³ /s (6.003 ft ³ /s)
Sound pressure level LpA (1 m) at 50/60 Hz	66 dB / 68 dB
Minimum short-circuit current ⁴⁾	4,400 A
Line length, max. ⁵⁾	
Shielded	2,600 m (8,530.18 ft)
Unshielded	3,900 m (12,795.28 ft)

¹⁾The base-load current DC IH is the basis for a duty cycle of 150% for 60 s or I max DC for 5 s with a duty cycle duration of 300 s.
³⁾The specified power loss represents the maximum value at 100% utilization. The value is lower under normal operating conditions.
⁴⁾Current required for reliably triggering protective devices.
⁵⁾Total of all motor cables and DC link. Longer cable lengths for specific configurations are available on request.