

## **Data sheet for SINAMICS G120P Cabinet**

MLFB-Ordering data: 6SL3710-1PG35-2CA0 \*\*

Client order no.: Order no.: Offer no.: Remarks:

Item no.: Consignment no.: Project:

Rated	data	

Input	
Supply frequency	4763 Hz
Supply voltage	690 V ±10%
Rated input current	499.0 A
Max. current	710 A
Pulse number	6
Energy recovery capability	No (2Q)

#### **Output:**

•	
Output voltage	690 V
Rated power (LO) in kW	450 kW
Rated power (HO) in kW	400 kW
Rated output current ***	480.0 A
Rated output current (LO) ***	470 A
Rated output current (HO) ***	394 A
Output current Max	682 A
Pulse frequency (nominal)	2.00 kHz

### Basic data:

Ambient temperature

Absolute power loss in stand-by	289 W
Sound pressure level L <sub>pA</sub> (1 m)	69 dB
Conductor cross section, max. (IEC)	4 x 240 mm²
Degree of protection	IP20
Installation envelope dimensions (H x W x	2300 mm x 1200 mm x 600 mm
Weight approx.	455 kg
Frame size	FSHX
Design	C (compact)
Color, paint shade	RAL7035
Compliance with standards	CE, RCM, EAC

0 °C - +40 °C


#### **Environmental conditions**

Installation altitude	1000 m
Coolant	Air
Coolant requirement, air	0.60 m³/s

#### Converter losses to IEC61800-9-2\*

IE2 Efficiency class

Comparison with the reference converter (90% / 100%) 39.2 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard IEC61800-9-2) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter including line choke without options/components.

# Special design

<sup>\*</sup>calculated values

<sup>\*\*</sup>EMC shield rail with PE rail and crane transport aid included in the standard scope of delivery

<sup>\*\*\*</sup>reduced value due to derating