Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	tvpe:	SE)200 NE	MA Pre	emium I	Next G	eneratio	on		FS	: RL449	T - 4p -	400 hp	-					
Motor type: SD200 NEMA Premium Next Generation Client order no. Item-No.								FS: RL449T - 4p - 400 hp - Offer no.											
Order no.						(Consignment no.					Project							
Remarks	lemarks																		
Electric	al data																		
U Δ/Υ f P [Hz] [HP]			P [kW]	n [rpm]	414	1	[Amps]		LDC	Nom. Eff Load [%] 4/4 3/4 2/4			Pw 4/4	r. Factor Lo	214		T _A /T _N	T _k /T _N	
[,1		[112]	[]	[KVI]	[16111]	4/4	3/4	1/2	0	LRC	., .	3/ 1	2/1	- '	3/1	2/ 1	[lb-ft]	LRT [%]	BDT [%]
_																			
Frame Type: RL449T Type of constr.				constr.:				Moto			Motor Prot	or Prot.:			NEMA Des.: S.F.		: 1.15		
N	Mtr. WT: lbs				Insulation Class.:				Temp. Rise Cl.: B			Amb. Temp.: + 40 to °C @1000 m				kVA:		IP	
Mecha	Mechanical data																		
Sound I	Sound level (SPL / SWL) at 60 Hz																		
				nd Cente	er Freque			`		Safe Stall Time Hot					s				
		250					4000	8000	Hz	Safe Stall Time Cold						S			
SP	L@3								dB(A)	Frame material						C	ast iron		
Momen	t of iner	rtia					Lb-ft²			Color,	paint sha	ade							
Ext Load	d Inertia	Capabilit	y:				Lb ft²			Coating (paint finish)									
Bearing										Ventilation Type									
1)E			N	J320		6315 Z C	3 SO	Method of cooling TEFC									
Bearing DE NDE NU320 Bearing_Type Roller Bearin						Bearing				Direction of rotation									
AFBMA: 100RU03M									Fan Material										
Grease										VFD CT: VT: 20:1									
Capacity 23 oz					3 oz	15 oz			Space heaters					without					
Grease Type:					72.22			Brake:							-/-				
	31																		
Termir	nal box	[
l	Lead Wire Connection							Termir	nal box p	osition									
Voltage L1 L2 L3 Connected together							Material of terminal box												
							Cable	entry					-/-						
										-									
Notes:																			
I _A /I _N = locke		rrent / current											eration with r	notor de	sign IC411				
		torque / torqu torque / nomi								2) at rate	d power / at	full load							
Responsible department Technical reference					ce	Created by			Appr	Approved by			Technical data are subject to change! There mo				nay be di	screpancies	
IN LVM	1				SPC							1_	Document status customer						
Document type													Document status				r		
Datasheet Document title 1LE6321-4UB2											Released								
				27.								Document number							
				0∠							Revision Creation date			Language Pag		Ie.			
© ABB 2024												01		2024-05-			1/1		

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	are prohibited. Offenders will	l be held liable for	r payment of
Responsible depar	tment	Technical reference	Created by	Approved by	be discrep	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Document type	<u> </u>	Created automatically			etatue	里 第	
	Document type Document status Wiring diagramm Released								
		Document title		Document	number				
		1LE6321-4UB2					0504-233418	□	1
Restricted		-				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-04	len	1/1