Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	rtvne:	SE	)200 NF	MA Pre	emium I	Next G	eneratio	n		FS	: 5.011	- 4p - 60	00 hp -						
Motor type: SD200 NEMA Premium Next Generation  Client order no. Item-No.									FS: 5,011 - 4p - 600 hp -  Offer no.										
liter							en No.						one no.						
Order no.						C	Consignment no.						Proje	ct					
Remarks																			
Electri	Electrical data																		
U Avy f P P n					I Load	[Amps]		Nom. Eff Loa			ıd [%]	Pw	r. Factor Lo	ad [%] Torque		T <sub>A</sub> /T <sub>N</sub>	T <sub>k</sub> /T <sub>N</sub>		
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 5,011 Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.	: 1.15		
Mtr. WT: lbs					Insulation Class.:				Tomp F	Pico Cl · P	Amb Tome : 40 to 00			or ത10	100 m	kVA:			ID
	IVILIT. WVI.II	ns			IIISulatio	JII Class.:			remp. r	use CI B	se Cl.: B Amb. Temp.: + 40 to °C @1000				,00 III	kVA: IP			IP
Mech	anical d	lata																	
Sound	laval (SD	L / SWL) a	ıt 60 Hz			di.	B(A) / dB	(Δ)		Thicke	nor					Po	lyurea		
Journa	ievei (3r			nd Cente	er Freque			(^)		mickener									
		250					4000	8000	Hz	Safe Stall Time Hot						S S			
S	PL@3								dB(A)	Safe Stall Time Cold						C	ast iron		
Mome	nt of ine	rtia					Lb-ft²			Frame material									
	Moment of inertia Lb-ft <sup>2</sup> Ext Load Inertia Capability: Lb ft <sup>2</sup>								Color, paint shade										
Bearin		Саравіні	.у.				LDTC			Coating (paint finish)									
l	_	NE.			6277	7 (2 50	. 1	6322 Z C	.5 60	Ventilation Type  Method of cooling TEFC									
Bearing DE   NDE 6322 Z C3 S										Direction of rotation									
Bearing_Type Ball Bearing					_				Fan Material										
AFBMA: 110BC03JP3 110BC03JP3							231. 2	VFD CT: VT: 20:1											
Grease 17 on					7.07	1	17 0-		Space heaters without					ı					
Capacity 17 oz Grease Type:				7 02	17 oz			Brake:				-/-							
Grease	: Type.									втаке:									
Termi	nal box	[																	
Lead Wire Connection Terminal box position																			
Voltage L1 L2 L3 Connected together							Material of terminal box												
								Cable entry -/-											
									cubic	circiy					,				
Notes:										2) (1)		(			. 15444				
$M_A/M_N = I$	ocked rotor	rrent / current torque / torqu torque / nomi	ue nominal								s valid only d power / at		eration with r	notor de	sign iC411				
Responsible department Technical reference Created by IN LVM SPC						ed by		Approved by Technical data are sul					bject to change! There may be discrepancies						
Document type Datasheet Document title 1LE6321-5AB0									Document status custome				r						
													Released						
											Document number				1				
					30														
												Revisi	on	Creation date		Languag			
© ABE	© ABB 2024											01		2024-05-	06 20:34	en	1/1	1	

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Decorate		Created automatically			ctatus		
Document type Document status Wiring diagramm Released									
		Document title		Document i	number	5,9°60 20022			
		1LE6321-5AB0					0506-203431		
Restricted		1			L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-06	en	1/1