| <u>Data</u> | sheet | t for th | nree-p | hase ! | Squirr | el-Cag | ge-Mo | tors Al | <u>BB</u> | | | | | | | | | | | |
|---|--|---------------------------------|---------|---------|-----------------------|-----------|--------------------|------------------------|-----------------------|--|-----------------------------------|-------------------|----------------|------------------------------|----------------|---------------|------------|---------|----------------|--|
| Moto | r type: | SE | 0200 NE | EMA Pre | emium I | Next G | eneratio | on | | FS | 5,012 | - 6p - 5(| 00 hp - | | | | | | | |
| Client order no. | | | | | | | Item-No. | | | | | <u> </u> | Offer no. | | | | | | | |
| | | | | | | | | | | | | | | | | | | | | |
| Order no. | | | | | | ſ | Consignme | nt no. | | | | | Proje | ct | | | | | | |
| Remarks | 5 | | | | | | | | | | | | | | | | | | | |
| Electri | cal data | a | | | | | | | | | | | | | | | | | | |
| | | | | | | [A] | | | | | | | | ad [%] Torque T _A | | | - (T | | | |
| $ \begin{array}{c c} U \\ [V] \end{array} \begin{array}{c c} \Delta/Y \end{array} \begin{array}{c c} f \\ [Hz] \end{array} \begin{array}{c c} P \\ [HP] \end{array} \begin{array}{c c} P \\ [KW] \end{array} \begin{array}{c c} n \\ [rpm] \end{array} \begin{array}{c} 4/4 \end{array} $ | | | 114 | 3/4 | [Amps] 1/2 | 0 | LRC | Nom. Eff Load [% | | | %] Pwr. Factor Loa 2/4 4/4 3/4 | | | ad [%] Torque 2/4 [lb-ft] | | | | | | |
| | | | | | | 4/4 | 5/4 | 1/2 | 0 | LINC | | | | | | | | LRT [%] | D DT[%] | |
| - Fra | me Type: 5 | - 012 | | | Turna ad | constr.: | | | | | | | Motor Prot | | | NEM | | | . 1.15 | |
| | ine type: : | 5,012 | | | Туре от | constr.: | | | | Motor | | | |)r Prot.: | | | NEMA Des.: | | S.F.: 1.15 | |
| | Mtr. WT: lk | bs | | | Insulation Class.: Te | | | | Temp. F | ise Cl.: B Amb. Temp.: + 40 | | | | 0 to °C @1000 m | | | kVA: | | IP | |
| Mech | anical d | lata | | | | | | | | | | | | | | | | | | |
| | | | | | | لہ | | | | Thisks | | | | | | F | Polyurea | | | |
| Sound | level (SP | L / SWL) a | | nd Cont | er Freque | | B(A) / dB | (A) | | Thicke | | llat | | | | | - | | | |
| | | 250 | | | | 000 | 4000 | 8000 | Hz | Safe Stall Time Hot | | | | s | | | | | | |
| S | PL@3 | | | | | | | | dB(A) | Safe Stall Time Cold Frame material | | | | | s Cast iron | | | | | |
| Mome | nt of iner | rtia | | | | | Lb-ft ² | | | | | | | | | | | | | |
| | | Capabilit | tv: | | | | Lb ft ² | | | Color, paint shade Coating (paint finish) | | | | | | | | | | |
| Bearin | | | | | | | | | | Ventilation Type | | | | | | | | | | |
| | g DE ND | DE | | | 6322 | Z C3 S0 | | Method of cooling TEFC | | | | | | | | | | | | |
| | g_Type | . – | | | | Bearing | | 6322 Z C Ball Bea | | Direction of rotation | | | | | | | | | | |
| AFBMA | | | | | | BC03JP3 | | 110BC03 | | Fan Material | | | | | | | | | | |
| Grease | | | | | | | 1 | VFD | | | | | | | | CI | : VT: 20 |)·1 | | |
| | | | | | 7 07 | 1 | 17 o: | 7 | Space heaters without | | | | | | | | | | | |
| Capacity 17 oz Grease Type: | | | | , 02 | | 17 0. | - | Brake: | | | | | -/- | | | | | | | |
| - Circuse | | | | | | | | | | Diake. | | | | | | | | | | |
| Termi | nal box | [| | | | | | | | | | | | | | | | | | |
| | Lead Wir | re Connec | tion | | | | | | | Termir | nal box p | osition | | | | | | | | |
| Voltage L1 L2 L3 Connected to | | | | | | ected tog | ether | - | | ninal bo> | (| | | | | | | | | |
| | | | | | | | | Cable | Cable entry | | | | | - | 1- | | | | | |
| | | | | | | | | | | - | | | | | | | | | | |
| | ked rotor cur | rrent / curren torque / torq | | | | | | | | | s valid only | | eration with r | notor de | sign IC411 | | | | | |
| | | torque / nomi | | | | | | | | , | , | | | | | | | | | |
| | esponsible department Technical reference Created by | | | | | | Appr | oved by | | | Tech | nnical data are s | subject to c | hange! There | e may be o | discrepancies | | | | |
| IN LVI | N LVM SPC | | | | | | | | | | | | | | | | | | | |
| Document type Datasheet Document title 1LE6321-5BC5 | | | | | | | | | | | | ment si | tatus | | custor | ner | | | | |
| | | | | | | | | | | | Released | | | | _ | | | | | |
| | | | | 5 | | | | | | | Docu | Document number | | | | | | | | |
| | | | | | | | | | | | Revisi | ion | Creation date | | Langua | age Pa | ge | | | |
| © ABB 2024 | | | | | | | | | | | | 01 | | 2024-05- | | | 190 11 | | | |

| Γ | | | Main ter | minal diagram | | | | | |
|---|--|--|--|-----------------------------------|------------------------|-----------------------|--|--------------------|---------------|
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| | | | | | | | | | |
| Transmitted and the first | an alta an to at the th | and the second | without an after | | h = / | | | | |
| i ransmittal, reproductio damages. All rights crea | on, dissemination and/or ited by patent grant or re | editing of this document as well as gistration of a utility model or desi | utilization of its contents and cor gn patent are reserved. | nmunication thereof to others wit | nout expre | ss authorization | are prohibited. Offenders will | i be held liable f | or payment of |
| Responsible departr | nent | Technical reference | Created by | Approved by | Technica | ıl data are subi | ect to change! There may en calculated and rating | Link docun | nents |
| IN LVM | | | , | Created automatically | be discre plate val | pancies betwe ues. | en calculated and rating | | |
| | | Document type | | 1 | 1 | Document status | | | |
| | Wiring diagramm Released | | | | | | | | |
| | | Document title | | | | Document number | | | |
| | | 1LE6321-5BC5 | | | | |)505-083037 | | 0.0000000 |
| Restricted | 0004 | | | | | Revision | Creation date | Language | Page |
| © Innomotics 2 | 2024 | ļ | | | | AA | 2024-05-05 | en | 1/1 |