Data	sheet	t for th	nree-p	hase !	Squirr	el-Cag	ge-Mo	tors Al	<u>BB</u>											
Moto	r type:	SE	0200 NE	EMA Pre	emium I	Next G	eneratio	on		FS	5,013	- 6p - 6(00 hp -							
Client order no.						I	Item-No.					Offer	Offer no.							
Order no.						(Consignme	nt no.					Proje	ct						
							5													
Remarks	5																			
Electri	cal data	3																		
$\begin{array}{c c} U & f & P & P & n \\ I V I & \Delta / Y & I V I & V D I & I V D I \\ \end{array}$					I Load	[Amps]		Nom. Eff Loa					r. Factor Lo			T_A/T_N	T_k/T_N			
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	1 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Fra	me Type: 5	5,013			Type of	constr.:							Motor Prot	.:		NEM	A Des.:	S.F	.: 1.15	
	Mtr. WT: lt	bs			Insulation Class.:				Temp. R	Rise Cl.: B Amb. Temp.: +			.: + 40 to '	40 to °C @1000 m			kVA:		IP	
Mech	anical d	ata																		
Sound	level (SP	L / SWL) a	at 60 Hz			d	B(A)/dB	(A)		Thicke	ner					P	olyurea			
					er Freque			8000		Safe Stall Time Hot s										
	PL@3	250) 50	10 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold					s					
									dB(A)	Frame material							Cast iron			
	nt of iner						Lb-ft ²			Color, paint shade										
	ad Inertia	Capabilit	ty:				Lb ft ²			Coating (paint finish)										
Bearin	-	_					. 1	Ventilation Type												
	g DE ND	θE				Z C3 S0)	6322 Z C		Method of cooling TEFC										
	g_Type					Bearing		Ball Bea		Direction of rotation										
AFBM/					110	BC03JP3		110BC03JP3 Fan Material												
Greas							1			VFD						CT: VT: 20:1				
Capacity 17 oz				7 oz		17 oz	Z	Space heaters					without -/-							
Grease	e Type:									Brake:						-1-				
Termi	nal box																			
	Lead Wir	re Conneo	ction							Tormir	nal box p	ocition								
Voltage L1 L2 L3 Connected togeth						ether	-		ninal box											
						5		Cable entry						1-						
								Cubic	citity											
Notes:	ked rotor cur	ront / arms	t nomin-l							2) \/al··- '	bilev	for DOL -:	vation with	notor	rian IC411					
$M_A/M_N =$	ked rotor cur locked rotor t break down t	torque / torqi	ue nominal								s valid only d power / at		ration with r	notor de	sign IC4 I I					
Respon	Responsible department Technical reference Created by						Appr	oved by			Tech	nnical data are s	subject to cl	nange! There	may be a	liscrepancies				
IN LVI	LVM SPC																			
Document type Datasheet Document title 1LE6321-5BC7								·			Docu	ment s	tatus		custom	ier				
												Released								
											Document number									
				./							curit i									
© ABB 2024												Revisi 01	IUTI	Creation date		Langua 1 en	ige Pa	ge 1		

			Main ter	minal diagram					
Transmittal, reproduct	ion, dissemination and/or	editing of this document as well as gistration of a utility model or desig	utilization of its contents and cor	nmunication thereof to others wit	hout expre	ss authorizatior	are prohibited. Offenders will	be held liable f	or payment of
aamayes. An rights cre	accu by patent grant of re	gistration of a utility model of desig	gn patern are reserved.						
Responsible depar	tment	Technical reference	Created by	Approved by	be discre	pancies betwe	ect to change! There may en calculated and rating	Link docun	<u>nents</u>
IN LVM				Created automatically	plate val	lues.		回渡	
		Document type		Document s	20				
	Wiring diagramm Released Document title Document number								
		1LE6321-5BC7				Document number WDS-240501-165107			
Restricted		· · · · · · · · · · · · · · · · · · ·				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-01	en	1/1
		!				I		<u> </u>	