Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor type: SD200 NEMA Premium Next Generation FS: 5011S - 4p - 600 hp -																			
Client order no.												Offer	Offer no.						
Order no.						-	Consignme	nt no.					Proje	Project					
Remarks																			
Electri	cal data	<b>a</b>																	
U						[Amps]		Nom. Eff Loa			d [%]	lwq	. Factor Lo			T <sub>A</sub> /T <sub>N</sub> T <sub>k</sub> /T <sub>N</sub>			
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Fran	Frame Type: 5011S Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F	.: 1.15	
	NAL MET II	ı.							T D	Tarra Diaz Cl. D. Arab Ta			40.1.	05.010	20	b//A -			
	Mtr. WT: lbs Insulation Class.				on Class.:			Temp. K	ise Cl.: B Amb. Temp.: + 4				C @100	JU M	KV	kVA:		IP	
Mecha	Mechanical data																		
																D	olvuroa		
Sound	level (SP	L / SWL) a					B(A) / dB	(A)		Thickener Polyurea									
		2 <b>5</b> 0			r Frequei <b>)00       2</b>	ncies He <b>000</b>	ertz <b>4000</b>	8000	Hz	Safe Stall Time Hot s									
C	PL@3	230	, 50	0 10	700 2	000	4000	8000		Safe Stall Time Cold							S Coot ivon		
31	rL@3								dB(A)	Frame material Cast iron									
Mome	Moment of inertia Lb-ft²									Color, paint shade									
Ext Loa	d Inertia	Capabilit	y:				Lb ft²			Coating (paint finish)									
Bearin	gs									Ventilation Type									
Bearing	g DE   ND	ÞΕ			6322	Z C3 S0	)	6322 Z C	3 SO	Method of cooling TEFC									
Bearing	Bearing_Type Ball Bearing Ball Bearing								ring	Directi	on of rot	ation							
AFBMA	AFBMA: 110BC03JP3 110BC03JP3								3JP3	Fan M	aterial								
Grease	•						,			VFD CT: VT: 20:1									
						17 oz Space heaters								without					
Grease Type:								Brake:							-/-				
Termi	nal box	(																	
	Lead Wire Connection							Termir	nal box p	osition									
Voltage L1 L2 L3 Connected together							ether	Material of terminal box											
									Cable entry -/-										
								:											
		rrent / current											ration with r	motor des	ign IC411				
		torque / torqu torque / nomi								∠) at rate	d power / at :	ıuli load							
I '	Responsible department Technical reference Created by SPC						Approved by Technical data				are subject to change! There may be discrepancies								
<u> </u>				Document type			ı					Docu	Document status custome			er			
	Datasheet											Released							
Document title												Document number				-			
1LE6321-5EB0					0														
									•			on	Creation date	9	Langua	ge Pa	ge		
© ABB 2024											01		2024-05-	05 13:28	en en	1/	1		

			Main te	minal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	be discrep	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM				Created automatically	plate valu	ies.		回次数	
	Document type Document status								
		Wiring diagramm	Released		200	<b>双</b> 赛			
		Document title				Document			
Doct-riet1		1LE6321-5EB0					0505-132840	Language	I Page
Restricted © Innomotics	2024					Revision AA	Creation date	Language en	Page 1/1