Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	rtvne:	SE)200 NF	-MA Pre	emium l	Next G	eneratio	n		FS	: 50135	- 4n - 8	300 hp -						
Motor type: SD200 NEMA Premium Next Generation Client order no. Item-No.								FS: 5013S - 4p - 800 hp - Offer no.											
Order no.						C	onsignme	nt no.					Proje	ect					
Remarks	Remarks																		
Electri	cal data	<u> </u>																	
U A/Y f P P n				I Load	[Amps]		Nom. Eff Loa				1	vr. Factor Lo			T _A /T _N T _k /T _N				
[V]	Δ/1	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	4 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 5013S Type of constr.:					constr.:				Mot			Motor Pro	or Prot.:			Des.:	S.F.	: 1.15	
	Mtr. WT: II	bs		Insulation Class.:					Temp. F	Rise Cl.: B	Cl.: B Amb. Temp.: + 40 to			°C @10	000 m	kVA:		IP	
	Tonp. III																		
Mecha	anical d	lata																	
Sound	level (SP	L / SWL) a	at 60 Hz			dl	B(A) / dB	(A)		Thicke	ner					Ро	lyurea		
Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Octave Band Center Frequencies Hertz								Safe Stall Time Hot s											
		250					4000	8000	Hz	Safe Stall Time Cold							S		
SI	PL@3								dB(A)	Frame material					Cast iron				
Momei	nt of ine	rtia					Lb-ft²			Color, paint shade									
Ext Loa	ad Inertia	Capabilit	tv:				Lb ft²			Coating (paint finish)									
Bearin			,							Ventilation Type									
l	g DE NC)E			6322	Z C3 S0		6322 Z C	.3 20	Method of cooling TEFC									
		/ L				Bearing				Direction of rotation									
Bearing						_		Ball Bea	-	Fan Material									
AFBMA					1106	3CO3JP3		110BC03	3JP3		aterial								
Grease										VFD CT: VT: 20:1									
Capacity 17 oz				7 oz		17 oz	Z	Space heaters				without							
Grease Type:										Brake:					-/-				
Termi	nal box	[
Lead Wire Connection Terminal box position																			
Voltad	Voltage L1 L2 L3 Connected together							ether	Material of terminal box										
.s.age E. EZ ES Connected together								Cable entry -/-											
									Cable	entry					-1-				
										-									
Notes:																			
		rrent / curren											eration with	motor de	esign IC411				
		torque / torqı torque / nomi								2) at rate	d power / at	full load							
Responsible department Technical reference					ce	Create	ed by		Approved by				Technical data are subject to change! To				nay be di	iscrepancies	
IN LVN	VI						SPC						T.	Document status customer					
	48				nent type									Document status				r	
Datasheet Document title 1LE6321-5FB8												Released							
				.0								Document number							
				8								n. M			<u> </u>	Language Page			
_ AD-												Revis	ion	Creation dat		Languag			
○ ARB	3 2024												01		ZUZ4-U5-	-05 23:35	en	1/1	I

			Main te	rminal diagram								
				•								
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	s utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	ithout expres	s authorization	are prohibited. Offenders will	be held liable for	r payment of			
Responsible depar	tment	Technical reference	Created by	Approved by	be discre	l data are subj pancies betwe	ect to change! There may en calculated and rating	Link docume	<u>ents</u>			
IN LVM		-		Created automatically	plate valu			回線				
	Document type Wiring diagramm Document title Document number											
								7780	双 赛			
Doct-riet1		1LE6321-5FB8					0505-233532	Language	I Page			
Restricted © Innomotics	2024					Revision AA	Creation date	Language en	Page 1/1			