Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	tvne:	SI)200 NE	-MA Pre	emium l	Next G	eneratio	n		FS	· R5010	- 6n - 3	50 hn -						
Motor type: SD200 NEMA Premium Next Generation Client order no. Item-No.								FS: R5010 - 6p - 350 hp - Offer no.											
Order no.							Consignment no.					Project							
Remarks																			
Electrical data																			
									l		101 2 5 1 101				T /T T /7		T		
U Δ/Υ f [Hz]			P P n [HP] [kW] [rpm			4/4	I Load [Amps]		0	LRC	Nom. Eff Load [%]			Pw 4/4	r. Factor Lo I 3/4	214		T _A /T _N LRT [%]	
						7/7	314	1/2	0	LINC							[ID-IL]	LIVI [%]	BD1 [%]
Frame Type: R5010 Type of constr.: Motor Prot.: NI										NEMA	Des :	S.F.	: 1.15						
Frame Type: R5010					Type of constr.:								WIOTOI 110t	•					. 1.15
	Mtr. WT: II	bs			Insulation Class.:				Temp. F	Temp. Rise Cl.: B Amb. T			.: + 40 to '	°C @10	000 m	kVA:			IP
Mecha	anical d	lata																	
		PL / SWL) a	at 60 Hz			q	B(A) / dB	(A)		Thicke	ner					Po	lyurea		
Journa	ievei (3i			nd Cente	er Freque			(//)				Hot					S		
		250				000	4000	8000	Hz							s			
S	PL@3								dB(A)	Frame material						C	ast iron		
Moment of inertia Lb-ft ²						Lb-ft²			Color, paint shade										
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish)									
Bearin										Ventilation Type									
l	- g DE NC)E			NU	J 322		6322 Z C	:3 SO	Method of cooling TEFC									
Bearing					Rollei	r Bearing	,	Ball Bear	ring	Direction of rotation									
AFBM <i>A</i>						RU03M0		110BC03	=	Fan Material									
Grease						ı			VFD CT: VT: 20:1										
Capacity 18 oz					8 oz		17 oz	Z	Space heaters					without					
Grease Type:								Brake:					-1-						
	31																		
Termi	nal box	(
Lead Wire Connection Terminal box position																			
Voltage L1 L2 L3 Connected together							Material of terminal box												
								Cable	entry					-/-					
											,								
Notes:	ked rotor cui	rrent / curren	t nominal							3) Value i	s valid only	for DOL one	eration with r	notor de	sign IC411				
$M_A/M_N = I$	ocked rotor	torque / torqu torque / nomi	ue nominal								d power / at				9				
Responsible department Technical reference					Created by			Appr	Approved by			Technical data are subject to chan				ge! There may be discrepancies			
Document type									Docu	ment st	atus		custome	r					
Datasheet											Released								
Document title 1LE6321-5RC2											Document number								
				2															
											Revision Creation date		e	Languag	e Pag	e			
© ABB 2024									0					2024-06-	04 12:32	en	1/1	l	

			Main te	rminal diagram					
Transmittal, reproduc	tion, dissemination and/or	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM				Created automatically	plate values.		ctatus	具数	
	Document type Wiring diagramm Released								
		Document title	- 1	Document	number	\$200 \$200			
		1LE6321-5RC2					0604-123225		
Restricted		1			L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-06-04	en	1/1