Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	tvpe:	SE) 200 NE	MA Pre	emium 8	341		FS: 445	T - 4p -	150 իթ	_								
Motor type: SD200 NEMA Premium 841 FS: 445T - 4p - Client order no. Item-No.							Offer no.												
Order no.						(Consignment no.						Project						
Remarks	Remarks																		
Electri	cal data																		
$ \begin{array}{ c c c c c c }\hline U & \Delta/Y & f & P\\ \hline [V] & \Delta/Y & [Hz] & [HP] \\ \hline \end{array} $		P [HP]	P [kW]	n [rpm]	4/4	I Load	[Amps]	0	LRC	Nom. Eff Load [%]			Pw 4/4	r. Factor Lo I 3/4	214	Torque [lb-ft]	T_A/T_N LRT [%]	T _k /T _N BDT [%]	
						., .	57.	- 72		Lite							[2[70]	55. [70]
Frame Type: 445T Type of constr.:								Mot			Motor Prot	tor Prot.:			Des.:	S.F.	: 1.15		
	Mtr. WT: II	bs		Insulation Class.:					Temp. Rise Cl.: B Amb. Ten			mb. Temp	.: + 40 to '	°C @10	000 m	kVA	kVA:		IP
Mech	Mechanical data																		
			s+ 60 ∐-z			4ı	D(V) 4D	(A)		Thicks	nor					Po	lyurea		
Sound	ievei (SP	PL / SWL) a		nd Cente	er Freque		B(A) / dB rtz	(A)		THERENCI									
		250					4000	8000	Hz							S			
S	PL@3								dB(A)	Frame material						C	ast iron		
Moment of inertia						Lb-ft²			Color, paint shade										
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish)									
Bearin										Ventilation Type									
l	- g DE NC	DE			6320	Z C3 S0		6315 Z C	:3 SO	Method of cooling TEFC									
Bearing_Type Ball Bearing						Bearing				Direction of rotation									
AFBMA: 100BC03JP3					-				Fan Material										
Grease									VFD CT: VT: 20:1										
Capacity 15 oz					5 oz		15 oz	Z	Space heaters without										
Grease Type:								Brake:					-/-						
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,									Druke.									
Termi	nal box	(
	Lead Wire Connection								Terminal box position										
Volta	Voltage L1 L2 L3 Connected together							ether	Material of terminal box										
								Cable	entry					-/-					
										-									
Notes:																			
$M_A/M_N = I$	ocked rotor	rrent / curren torque / torqu torque / nomi	ue nominal								s valid only d power / at		eration with r	notor de	sign IC411				
Responsible department Technical reference					Create	Created by			Approved by			Technical data are subject to chan				nge! There may be discrepancies			
				Document type							R			Document status custome Released Document number				er	
Datasheet																			
Document title 1LE6322-4BB2									-										
				32															
											sion Creation date		Languag	Language Page					
© ABB 2024											01		2024-05-	03 00:38	en	1/	1		

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co- ign patent are reserved.	mmunication thereof to others wit	thout expres	ss authorizatior	are prohibited. Offenders will	be held liable for	r payment of
December 21 to the control of the co		IT. belod of an an	I controll	I.a	T	l d-4		Learning	
Responsible depar	tment	Technical reference	Created by	Approved by Created automatically	be discre plate valu	i aata are subj pancies betwe ues.	ect to change! There may en calculated and rating	Link docume	<u>ents</u>
		Document type	<u> </u>	Created automatically	1	Document :	status		
	Wiring diagramm Released								20.25
		Document title	Document i	number					
		1LE6322-4BB2				WDS-240	0503-003840		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	len	1/1