Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	tvpe:	SE) 200 NE	MA Pre	emium 8	341		FS: 449	TS - 2p	- 250 hı	o -								
Motor type: SD200 NEMA Premium 841 FS: 449TS - 2p Client order no. Item-No.							Offer no.												
Order no.						(Consignment no.						Project						
Remarks	lemarks																		
Electri	cal data																		
U Δ/Y f P P n [Hz] [HP] [kW] [rpm] 4/			414	I Load [Amps]			1.0.6	Nom. Eff Load [%]						.	T _A /T _N T _k /T _N				
[*]		[112]	[]	[KVV]	[ibiii]	4/4	3/4	1/2	0	LRC	., .	3/ 1	2/ 1	.,	3/1	2/4	[lb-ft] l	RT [%]	BDT [%]
Frame Type: 449TS Type of constr.:											Motor Prot	.:		NEMA I	Des.:	S.F.:	1.15		
Mtr. WT: lbs				Insulation Class.:					Temp. Rise Cl.: B Amb. Te			mb. Temr).: + 40 to '	°C @10	100 m	kVA	kVA:		P
						on classii	: Temp. Rise				e Cl.: B Amb. Temp.: + 40 to °C @1000 m					KV/L II			
Mecha	anical d	lata																	
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																		
					r Freque					Safe Stall Time Hot s									
	PL@3	250	50	0 10	000 2	000	4000	000 8000 Hz			Safe Stall Time Cold				s -				
									dB(A)	Frame material						Cast iron			
	nt of ine						Lb-ft²			Color, paint shade									
		Capabilit	ty:				Lb ft²			Coating (paint finish)									
Bearin	_	\F			6245	7.62.60	. 1	6245.7.6		Ventilation Type									
	g DE NC)E				Z C3 S0		6315 Z C		Method of cooling TEFC									
Bearing						Bearing				Direction of rotation									
AFBMA: 75BC03JP3							75BC03	JP3	Fan Material										
Grease					_	1	45		VFD CT: VT: 20:1										
Capacity 15 oz				5 OZ	15 oz									vithout -/-					
Grease Type:									Brake:							,			
Termi	nal box	[
Lead Wire Connection Termin								nal box p	osition										
Voltage L1 L2 L3 Connected together							Material of terminal box												
								Cable	entry					-/-					
										_									
Notes:																			
		rrent / curren torque / torqu									s valid only d power / at		eration with r	notor de	sign IC411				
		torque / nomi	inal torque	Tarka:	!		Const	- J L		1,				Toch	nical data are	subject to cha	ngol Thoro m	av ho die	cronancios
Responsible department Technical reference IN LVM				ce	Create SPC	eu υy		Appr	Approved by			Technical data are subject to change! There may be discrep					ziepuncies		
Document type Datasheet									I				Document status Released						
Document title 1LE6322-4GA2											Document number]				
				A2															
												Revisi	ion	Creation date		Language	1 -		
© ABB	© ABB 2024											01		2024-05-	03 07:48	en	1/1		

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	are prohibited. Offenders will	l be held liable for	r payment of
		I=	T- ··	1	1			T	
Responsible depar	tment	Technical reference	Created by	Approved by	Technical be discrep plate valu	aata are subj pancies betwe ues.	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
III EVIVI		Document type	<u> </u>	Created automatically		Document	status	具数	
	Wiring diagramm Released								20.5
		Document title		Document	number				
		1LE6322-4GA2					0503-074839		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	len	1/1