Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:	SE)200 NE	MA Pre	emium 8	341		FS: L44	9TS - 2r	o - 350 ł	ıp -									
Motor type: SD200 NEMA Premium 841 FS: L449TS - 2 Client order no. Item-No.							Offer no.													
Order no.						(Consignment no.						Project							
Remarks	temarks																			
Electri	cal data	<u> </u>																		
U Δ/Υ f [Hz]		P [HP]					[Amps]	0	LRC	Nom. Eff Load [%]			Pw 4/4	r. Factor Lo 3/4	2/4	.	T _A /T _N .RT _[%]	T _k /T _N BDT [%]		
							3/4											[70]	[,0]	
Frame Type: L449TS Type of constr.:								Mot			Motor Prot	or Prot.:			Des.:	S.F.:	1.15			
Mtr. WT: lbs				Insulation Class.:					Temp. Rise Cl.: B Amb. Tem			mb. Temp	.: + 40 to '	°C @10	100 m	kVA:		ı	Р	
Mecha	Mechanical data																			
	Sound level (SPL / SWL) at 60 Hz																			
	•			nd Cente	er Freque					Safe Stall Time Hot s										
		250	50	0 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold						S				
SI	PL@3								dB(A)	Frame material					C	ast iron				
Mome	nt of iner	tia					Lb-ft²			Color, paint shade										
Ext Loa	d Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish)										
Bearin	gs									Ventilation Type										
Bearing	DE ND	ÞΕ			6315	Z C3 S0		6315 Z C	3 S0	Method of cooling TEFC										
Bearing_Type Ball Bearing					Bearing	g Ball Bearing			Direction of rotation											
AFBMA: 75BC03JP3						CO3JP3		75BC03	JP3	Fan Material										
Grease							,			VFD CT: VT: 20:1										
Capacity 15 oz				5 oz	15 oz			Space heaters w						vithout						
Grease Type:									Brake: -/-											
Termi	nal box																			
			ction							Tormis	aal boy n	ocition								
-	Lead Wire Connection Voltage L1 L2 L3 Connected together							ether	Terminal box position Material of terminal box											
							Cable entry -/-													
									Cable	entry					-1-					
										-										
Notes:																				
$I_A/I_N = lock$		rent / current											eration with r	notor de	sign IC411					
		torque / torqu orque / nomi								2) at rate	d power / at	full load								
Responsible department Technical reference IN LVM					Created by			Appr	Approved by			Technical data are subject to change! Th				ay be dis	screpancies			
				Document type									Document status customer							
Document type Datasheet													Released Document number							
Document title 1LE6322-4HA1																				
				\1																
												Revision Creation date		9	Language	Pag	e			
© ABB 2024										01		2024-05-	19 05:26	en	1/1					

l [Main te	rminal diagram					
				•					
[
Transmittal, reproduct	ion, dissemination and/or	editing of this document as well a	s utilization of its contents and co	mmunication thereof to others wit	ithout expres	s authorization	are prohibited. Offenders will	be held liable for	r payment of
Responsible depart	ment	Technical reference	Created by	Approved by	Technical be discre	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	ents
IN LVM				Created automatically	plate valu	ies.		□ (%)	
	Document type Document status							1	
		Wiring diagramm		Released		50000	双 赛		
		Document title				Document i		29	
		1LE6322-4HA1					0519-052635		- martin
Restricted © Innomotics	2024					Revision	Creation date 2024-05-19	Language	Page 1/1
• COHOMONICS	ZUZ4	i				AA	1 2 0 2 4 - 0 3 - 1 9	len	1 1/1