

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS  Motor type: 1AV2131A  SIMOTICS GP - 132 S - IM B5 - 2p																		
Motor Client ord		IAV21	ΣIA		Ite	em-No.	SINIOTICS GP	- 132 S	- IIVI B5	- <b>z</b> p	Offe	r no.						
0.4.						Consignment no. Project												
Order no					Co							Project						
Remarks					I						-							
FL												e Area						
	cal dat							1			-/-				T	1		
U	Δ/Υ	f	P	P	[ [ ]	n [1/min	M [Mm]	4/4	η <sup>3)</sup>	2/4	4/4	cosφ <sup>3)</sup>	2/4	I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>		IE-CI	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]		155/	3/4	2/4	4/4	3/4	2/4	I <sub>I</sub> /I <sub>N</sub>	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>	<u> </u>	
400	Δ	50	7.50	-/-	14.10	2950	OL duty (S1) 24.5	- 155(F 88.1	88.5	87.6	0.87	0.81	0.70	7.5	2.2	3.1	IE2	
690	Y	50	7.50	-/-	8.20	2950	24.5	88.1	88.5	87.6	0.87	0.81	0.70	7.5	2.2	3.1	IE2	
460	Δ	60	8.60	-/-	13.70	3550	23.0	89.5	90.1	89.6	0.88	0.85	0.78	7.4	2.0	3.1	IE2	
460	Δ	60	7.50	-/-	12.10	3560	20.0	89.5	89.7	88.7	0.87	0.83	0.74	8.2	2.3	3.6	IE2	
IM B5 / I	IM 3001		FS 132	S		IP55	UKCA	IEC/EN	60034		IEC, DIN, I	SO, VDE, EN						
		Enviro	nmental c	onditions :	-20 °C - +4	0 °C / 1	000 m			Lo	cked ro	tor time (	(hot / co	ld) : 8.8	3 s   14.3	s		
Mecha	nical c	data																
Sound	level (S	PL / SWL)	) at 50Hz 6	0Hz 68	/ 80 dB(A) <sup>2)</sup>	<sup>3)</sup> 72	/ 84 dB(A) <sup>2) 3)</sup>	Vibr	ation sev	erity grad	e				Α			
Moment of inertia					0.0240 kg m <sup>2</sup>				Thermal class					F				
Bearing DE   NDE					6208 2Z C3 6208 2Z C3				Duty type				S1					
bearin	ıg lifetir	me			-			Direction of rotation					bidirectional					
L <sub>10mh</sub> F	Rad min fo	r couplir	ng operatio	n	40000 h 32000 h				Frame material				aluminum					
	nz ·· nsing de				Without				Net weight of the motor (IM B3)				43 kg					
Grease	nipple				-1-				Coating (paint finish)				Standard paint finish C2					
Туре о	f bearin	g			Preloaded bearing DE				Color, paint shade				RAL7030					
Condensate drainage holes					Without				Motor protection				(A) without (Standard)					
Extern	al earthi	ing term	inal		Without				Method of cooling					IC411 - self ventilated, surface cooled				
Termir	nal box	<b>(</b>																
Terminal box position					top				Max. cross-sectional area				6 mm²					
Material of terminal box					Aluminium				Cable diameter from to				11 mm - 21 mm					
	f termin				TB1 H00				Cable entry				2xM32x1,5					
	ct screw				M4				e gland				2 plugs					
$M_A/M_N = Ic$	cked rotor	•	que nominal		) L <sub>10mh</sub> according 1 ) at rated power I		1 10/2010			3) V	alue is valid	only for DOL (	operation wi	th motor de	sign IC411			
			ninal torque semination and	or editing of this			of its contents and c						re prohibited	. Offenders	will be held li	able for payı	ment of	
Resnonsi	ihle dens	rtment		Technical ref	T	Created by		Approved					chanae! Th	ere mav be	Link doc	uments		
Responsible department Technical reference IN LVM					arence.	SPC SPC						al data are subject to change! There may be uncies between calculated and rating plate				#THEFT	<del></del>	
				Document ty	pe	<u> </u>						ocument status						
CIENAENIC Tec			Technical	echnical data sheet						Rele	Released					英		
				Document tit	cument title E1001-1CA13-4FA4						Docu	ment numb	er		i i			
				1LE1001-							TDS-240502-075				75152			

Creation date

2024-05-02

Revision

Language

Page 1/1

Restricted