## Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

<u>Data</u>	sheet	<u>t for tl</u>	hree-pha	ase Squi	irrel-Cao	ge-Moto	rs SIMO	<u>FICS</u>										
Motor type : 1AV3094C Client order no. Order no.						SIMOTICS GP - 90 L - IM B5 - 6p												
						Item-No. Consignment no.						Offer no. Project						
Electri	cal dat	a									-/-							
U	Δ/Υ	f	Р	Р	I	n	М		η 3)			cosφ <sup>a</sup>	1	I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>		IE-CL	
[V]		[Hz]	[kW]	[hp]	[A]	[1/min] [Nm]		4/4	3/4	2/4	4/4	3/4	2/4	I <sub>I</sub> /I <sub>N</sub>	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>		
DOL duty (S1)         155(F) to 130(B)           220         A         E0         111         81.0         81.4         70.2         0.66         0.67         0.44         E0         2.8														2.0	102			
230 400	Δ Y	50 50	1.10 1.10	-/-	5.20 2.95	950 950	11.1 11.1	81.0	81.4 81.4	79.3 79.3	0.66	0.57	0.44	5.0 5.0	2.8	3.0 3.0	IE3	
+00		50	1.10	,	2.55	550	11.1	01.0	01.4	79.5	0.00	0.57	0.11	5.0	2.0	5.0		
IM B5 / IM 3001 FS 90 L						IP55	UKCA	IEC/EN	IEC/EN 60034 IEC, DI				DIN, ISO, VDE, EN					
Environmental conditions : -20 °C -						40 °C / 10		Lo	Locked rotor time (hot / cold) : 31.8 s   40.5 s									
Mecha	nical d	lata																
Sound	level (SI	PL / SWL)	at 50Hz 60	Hz 43	/ 55 dB(A) <sup>2</sup>	<sup>3)</sup> 46/	58 dB(A) 2) 3)	Vibr	Vibration severity grade A									
Mome	nt of ine	ertia			0.	0052 kg m²		The	Thermal class				F					
Bearing DE   NDE 6205 2Z C						6	004 2Z C3	Duty	Duty type				S1					
bearing lifetime								Dire	Direction of rotation				bidirectional					
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 40000 h							32000 h	Fran	Frame material				aluminum					
Regreasing device						Without Net we				weight of the motor (IM B3)				19 kg				
Grease nipple						-1-		Coat	Coating (paint finish)				Standard paint finish C2					
Type of bearing Prel						ded bearing	J DE	Colo	r, paint s	hade		RAL7030						
Condensate drainage holes						Without		Mot	Motor protection				(B) 1 PTC thermistor - for tripping (2 terminals)					
External earthing terminal						Without Method of cooling						IC411 - self ventilated, surface cooled						
Termir	nal box																	
Termin	al box p	osition				top Max. cross-sectional area					ea	1.5 mm <sup>2</sup>						
Material of terminal box						luminium	Cab	Cable diameter from to				9 mm - 17 mm						
Type of terminal box						TB1 E00 Cable entry						1xM25x1,5-1xM16x1,5						
Contact screw thread						M4 Cable gland						2 plugs						
$M_A/M_N = Io$ $M_K/M_N = br$	cked rotor i eak down t	rrent / curre torque / torc corque / nom	ue nominal iinal torque	2)	) at rated power								DL operation wi					
Transm	ittal, repro	duction, dis	semination and/o	or editing of this			f its contents and patent grant or re						are prohibited	. Offenders	will be held l	iable for pay	yment of	
Responsi	ble depar	tment	[	Technical refe	erence	Created by Approved by					Technical data are subject to change! There mo				Link doo	<u>uments</u>		
IN LVM						SPC Created automatically discrepa						ncies between calculated and rating plate					St⊡	
Document type					pe						Docu	Document status						
SIEMENS Technical data she						et						Released						
Document title						D.4						Document number TDS-240519-050536						
Restrict	ed			ILE 1003-	UEC42-2F	D4					TDS Revis		9-050530		Languag	ge Page	e	
© Inno		2024									AA		2024-05-1		en	1/1		