## Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



SIMOTICS GP - 160 M - IM B35 - 2p Motor type : 1AV3163A Offer no. Client order no. Item-No Order no. Consignment no. Project Remarks Safe Area Electrical data -/-U Δ/Υ f Р Р ī М η 3)  $cos\phi^{\ 3)}$  $I_A/I_N$ M<sub>A</sub>/M<sub>N</sub>  $M_K/M_N$ IE-CL n [V] [Hz] [kW] [hp] [A] [1/min] [Nm] 4/4 3/4 4/4 2/4  $I_I/I_N$  $T_I/T_N$  $T_B/T_N$ 2/4 3/4 **DOL duty (S1)** - 155(F) to 130(B) 400 Δ 50 15.00 27.50 2955 48.5 91.9 91.9 90.8 0.86 0.81 0.71 10.2 3.5 4.4 IE3 690 50 15.00 -/-15.90 91.9 91.9 90.8 0.81 10.2 2955 48.5 0.86 0.71 3.5 4.4 IE3 Δ 460 60 17.30 -/-27.00 3550 46.5 91.7 91.4 90.2 0.88 0.84 0.75 4.5 IE3 10.1 3.3 Δ 4.0 IE3 460 60 15.00 24.00 3560 40.0 91.0 90.4 88.5 0.86 0.81 0.71 11.8 5.2 IM B35 / IM 2001 UKCA IEC/EN 60034 IEC, DIN, ISO, VDE, EN FS 160 M Environmental conditions: -20 °C - +40 °C / 1000 m Locked rotor time (hot / cold): 13.3 s | 18.9 s Mechanical data 77 / 85 dB(A) 2) 3) Sound level (SPL / SWL) at 50Hz|60Hz 81 / 89 dB(A) 2) 3) Vibration severity grade Α Thermal class Moment of inertia 0.0430 kg m<sup>2</sup> F Bearing DE | NDE **S**1 6209 2Z C3 6209 2Z C3 Duty type bearing lifetime Direction of rotation bidirectional  $L_{10mh}\,F_{Rad\,\,min}$  for coupling operation  $50|60Hz^{\,1)}$ 40000 h 32000 h Frame material aluminum Regreasing device Without Net weight of the motor (IM B3) 78 kg Grease nipple Coating (paint finish) Standard paint finish C2 Locating bearing NDE Color, paint shade RAL7030 Type of bearing Condensate drainage holes Without Motor protection (B) 3 PTC thermistors - for tripping (2 terminals) External earthing terminal Without Method of cooling IC411 - self ventilated, surface cooled Terminal box Terminal box position top Max. cross-sectional area  $16 \, mm^2$ Material of terminal box Aluminium Cable diameter from ... to ... 19 mm - 28 mm Type of terminal box TB1 J00 2xM40x1,5-1xM16x1,5 Cable entry Cable gland Contact screw thread М5 3 plugs 1) L<sub>10mh</sub> according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411 I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal 2) at rated power / at full load M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / torque nominal M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LVM	Technical reference	SPC	rippioted by		data are subject to change! There may be cies between calculated and rating plate		Link docume	ents
SIEMENS	Document type			Document status				
	Technical data sheet				Released			
	Document title				Document number			
	1LE1003-1DA33-4JB4			TDS-240523-232011				
Restricted					Revision	Creation date	Language	Page
© Innomotics 2024					AA	2024-05-23	en	1/1