

			-	iase Squ	irrel-Cag		ors SIMOT		INA DA A	1 2n						CC			
Client ord		: 1AV31	04A		It	SIMOTICS GP - 160 L - IM B14 - 2p  Item-No.						Offer no.							
Order no					C	Consignment no.						Project							
Remarks																			
Electri	cal da	ta									Saf -/-	e Area							
U \Delta IY f P			P	I	n M		η <sup>3)</sup>			cos		οsφ <sup>3)</sup> Ι <sub>Α</sub> /Ι <sub>Ν</sub>		M <sub>A</sub> /M <sub>N</sub> M <sub>K</sub> /M <sub>N</sub> IE-0		IE-CL			
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I <sub>I</sub> /I <sub>N</sub>	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>			
				1	1	DC	L duty (S1)	- 155(F	) to 130	)(B)									
400	Δ	50	18.50	-/-	32.00	2955	60.0	92.4	92.8	92.4	0.90	0.87	0.80	9.0	2.8	4.2	IE3		
690	Δ	50	18.50	-/-	18.60	2955	60.0	92.4	92.8	92.4	0.90	0.87	0.80	9.0	2.8	4.2	IE3		
460 460	Δ	60	18.50	- -	32.00 28.50	3555 3560	57.0 49.5	91.7	91.5 91.5	90.3	0.91	0.88	0.80	9.0	2.6 3.0	4.2	IE3		
IM B14 /		60	FS 160		26.50	1P55	UKCA	JEC/EN		90.3		SO, VDE, EN		10.2	3.0	4.0	IES		
					ions : -20 °C - +40 °C / 1000 m									(hot / cold) : 13.5 s   19.9 s					
Mecha	nical																		
Sound	level (S	SPL / SWL	) at 50Hz 6	0Hz 70	/ 82 dB(A) <sup>2)</sup>	<sup>3)</sup> 77 /	89 dB(A) <sup>2) 3)</sup>	Vibra	ation sev	erity grad	le				Α				
Mome	nt of in	ertia			0.0680 kg m²				Thermal class					F					
Bearing DE   NDE				(	6209 2Z C3 6209 2Z C3				Duty type				S1						
bearing lifetime					0207 22 63			-	Direction of rotation				bidirectional						
L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup>				n	40000 h 32000 h				Frame material				aluminum						
50 60Hz <sup>1)</sup> Regreasing device					Without				Net weight of the motor (IM B3)				94 kg						
Grease nipple					-/-				Coating (paint finish)				Standard paint finish C2						
Type of bearing					Locating bearing NDE				Color, paint shade				RAL7030						
Condensate drainage holes					Without				Motor protection				(A) without (Standard)						
External earthing terminal					Without				Method of cooling				IC411 - self ventilated, surface cooled						
Termir	nal box	×																	
Termir	nal box	position				top		Max.	cross-se	ctional a	rea				16 mm²				
Material of terminal box					Aluminium				Cable diameter from to				19 mm - 28 mm						
Type of terminal box					TB1 JOO				Cable entry				2xM40x1,5						
Contact screw thread					M5				Cable gland				2 plugs						
$M_A/M_N = 10$ $M_K/M_N = bi$	cked rotor reak down	torque / nor	que nominal minal torque	2	L <sub>10mh</sub> according ) at rated power document as we	l at full load	10/2010 of its contents and c	ommunicatio	n thereof to			only for DOL				able for payr	ment of		
						ights created by	patent grant or reg	gistration of a	utility mode						,				
Responsible department Technical reference IN LVM				erence				discrept			al data are subject to change! There may be ancies between calculated and rating plate				<u>uments</u>				
IIN LVIVI				Document tv	cument type							Document status Released							
	SIEMENS				echnical data sheet														
5					ocument title							Document number					靈		
				1LE1003-	.E1003-1DA43-4KA4					TDS-24050									

Creation date

2024-05-06

Language

Page

1/1

Revision

Branding disclaimer applies
-----------------------------

© Innomotics 2024

Restricted