## Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



SIMOTICS GP - 160 M - IM B35 - 4p Motor type: 1AV3162B Offer no. Client order no. Item-No Order no. Consignment no. Project Remarks Safe Area Electrical data -/η 3) Δ/Υ U f Р Р ī М cosφ <sup>3)</sup>  $I_A/I_N$ M<sub>A</sub>/M<sub>N</sub>  $M_K/M_N$ IE-CL n [V] [Hz] [kW] [hp] [A] [1/min] [Nm] 4/4 3/4 4/4  $I_I/I_N$  $T_I/T_N$  $T_B/T_N$ 2/4 3/4 2/4 **DOL duty (S1)** - 155(F) to 130(B) 400 Δ 50 11.00 21.00 1470 71.0 91.4 91.9 91.9 0.82 0.76 0.65 8.0 2.5 3.5 IE3 690 11.00 -/-12.30 1470 91.9 0.76 3.5 50 71.0 91.4 91.9 0.82 0.65 8.0 2.5 IE3 Δ 460 60 12.60 -/-20.50 1765 68.0 92.4 92.9 92.6 0.78 0.68 IE3 0.83 8.1 3.3 3.5 Δ IE3 460 60 11.00 1775 59.0 92.6 92.0 0.81 0.75 0.63 9.0 3.8 4.0 18.40 92.4 IM B35 / IM 2001 UKCA IEC/EN 60034 IEC, DIN, ISO, VDE, EN FS 160 M Environmental conditions: -20 °C - +40 °C / 1000 m Locked rotor time (hot / cold): 26.5 s | 34.3 s Mechanical data 67 / 75 dB(A) 2) 3) Sound level (SPL / SWL) at 50Hz|60Hz 70 / 75 dB(A) 2) 3) Vibration severity grade Α Moment of inertia 0.0583 kg m<sup>2</sup> Thermal class F Bearing DE | NDE 6209 2Z C3 6209 2Z C3 Duty type S1 bearing lifetime Direction of rotation bidirectional  $L_{10mh}\,F_{Rad\,\,min}$  for coupling operation  $50|60Hz^{\,1)}$ 40000 h 32000 h Frame material aluminum Regreasing device Without Net weight of the motor (IM B3) 78 kg Coating (paint finish) Standard paint finish C2 Grease nipple Locating bearing NDE RAL7030 Type of bearing Color, paint shade Condensate drainage holes Without Motor protection (B) 3 PTC thermistors - for tripping (2 terminals) External earthing terminal Without Method of cooling IC411 - self ventilated, surface cooled Terminal box Terminal box position top Max. cross-sectional area  $16 \, mm^2$ Material of terminal box Aluminium Cable diameter from ... to ... 19 mm - 28 mm Type of terminal box TB1 J00 2xM40x1,5-1xM16x1,5 Cable entry Contact screw thread М5 Cable gland 3 plugs 1) L<sub>10mh</sub> according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411 IA/IN = locked rotor current / current nominal 2) at rated power / at full load M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / torque nominal M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved. Technical data are subject to change! There may be Responsible department Technical reference Created by Approved by Link documents discrepancies between calculated and rating plate IN LVM SPC Created automatically values.

SIEMENS	Technical data sheet	Released			
	Document title	Document number			
	1LE1003-1DB23-4JB4	TDS-240426-161249			
Restricted		Revision	Creation date	Language	Page
© Innomotics 2024		AA	2024-04-26	en	1/1