## Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Page

Language

Revision

Creation date

2024-05-20

Data	shee	t for t	hree-ph	iase Squi	irrel-Cag	e-Moto	rs SIMOT	<u>ICS</u>								CC			
Motor	type :	: 1AV31	64B			SI	MOTICS GP	) - 160 L	- IM B35	i - 4p						.0			
Client or	der no.				lte	Item-No.						Offer no.							
Order no.						Consignment no.						Project							
Remarks																			
Electri	ical dat	ta									Sa -/-	fe Area							
U	Δ/Υ	f	Р	Р	I	n	М		η 3)			cosφ <sup>3)</sup>		I <sub>A</sub> /I <sub>N</sub>	M <sub>A</sub> /M <sub>N</sub>	M <sub>K</sub> /M <sub>N</sub>	IE-CL		
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I <sub>I</sub> /I <sub>N</sub>	T <sub>I</sub> /T <sub>N</sub>	T <sub>B</sub> /T <sub>N</sub>			
			I				L duty (S1)	1			ı			ı			ı		
400	Δ	50	15.00	-/-	28.50	1465	98.0	92.1	92.7	92.0	0.83	0.78	0.67	7.9	2.8	3.4	IE3		
690 460	Δ	50 60	15.00	-l- -l-	16.40 28.50	1465 1765	98.0 94.0	92.1	92.7 92.5	92.0 92.0	0.83	0.78	0.67	7.9	2.8	3.4	IE3		
460	Δ	60	15.00	-/-	25.00	1775	81.0	93.0	92.9	92.0	0.83	0.79	0.69	8.9	3.1	3.8	IE3		
	IM 2001	00	FS 160		25.00	IP55	UKCA		1 60034	72.1		ISO, VDE, EN		0.5	3.1	3.0	ILS		
		Enviro	nmental c	onditions :	-20 °C - +4	+0 °C / 10	00 m			Locked rotor time (hot / cold) : 24					6 s   33.	3 s			
Mecha	anical c	data																	
Sound	level (S	PL / SWL)	) at 50Hz 6	OHz 58	/ 66 dB(A) <sup>2)</sup>	<sup>3)</sup> 66 /	74 dB(A) <sup>2) 3)</sup>	Vibr	ation seve	erity grad	e				Α				
·						)890 kg m²		The	rmal class		F								
Bearing DE   NDE 6209 2Z						6	209 2Z C3	Dut	y type		\$1								
bearing lifetime								Dire	Direction of rotation				bidirectional						
L <sub>10mh</sub> F	Rad min fo	r couplir	ng operatio	n	40000 h		32000 h	Fran	Frame material				aluminum						
	asing de				V	Without			Net weight of the motor (IM B3)				106 kg						
Grease	e nipple				-/-			Coa	Coating (paint finish)				Standard paint finish C2						
Type c	of bearin	g			Locatir	Locating bearing NDE			Color, paint shade				RAL7030						
Condensate drainage holes					Without				Motor protection				(A) without (Standard)						
External earthing terminal					Without			Met	Method of cooling				IC411 - self ventilated, surface cooled						
Termi	nal box	(																	
Terminal box position						top			Max. cross-sectional area				16 mm²						
Material of terminal box					Al	Cable diameter from to				. 19 mm - 28 mm									
Туре с	of termin	nal box			-	TB1 J00		Cab	Cable entry				2xM40x1,5						
Conta	ct screw	thread				M5	Cab	Cable gland				2 plugs							
$M_A/M_N = 10$ $M_K/M_N = b$	ocked rotor reak down	torque / nor	que nominal minal torque	2)	) L <sub>10mh</sub> according t ) at rated power /	at full load		communi	on there-f+			only for DOL				iable for	mont of		
ıransn	ınıtal, repro	rauction, dis	semmation and	or earling of this			of its contents and of patent grant or re						re pronibited	. Onenders	wiii be neid l	iauie tor payt	ment of		
Responsible department Technical reference									discrep			cal data are subject to change! There may be nancies between calculated and rating plate				Link documents			
IN LVM						SPC		Created	automatic	ally valu	ies.			any piate			<b>X</b>		
				Document type Technical data sheet							Document status Released								
				Document tit							Document number								
					LE1003-1DB43-4JA4					TDS-240520-2				5					
				1	בביסטו סיים דאתד					2				Creation data			I I.a		

Restricted