<u>Data</u>	sheet	t for th	iree-p	hase	Squirro	el-Cao	ge-Mot	ors A	<u>BB</u>											
Motor	type:				FS: 1	43T - p	- 1.5 hp) -												
Motor type: FS: 143T - Client order no.							Item-No.					Offer	Offer no.							
Order no.							Consignment no.					Proje	Project							
Remarks																				
Electri	cal data	3																		
U					[Amps]					ff Load [%] Pwr. Factor Lo				[%] Torque		T _k /T _N				
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
											1									
Fra	me Type: '	143T			Type of	constr.:							Motor Prot	.:		NEM	A Des.:	S.F.	: 1.15	
	Mtr. WT: lk	bs	l	Insulation Class.:Standard Class F Insulation Ten					Temp. I	Rise Cl.: B Amb. Temp.: + 40 to -20 °C @)°C @10	100 m	n kVA:			IP 55	
Mech	anical d	lata																		
Sound	level (SP	L / SWL) a	it 60 Hz			d	B(A) / dB(A)		Thicke	ner									
		C	ctave Ba	nd Cente	er Freque	ncies He	ertz			Safe Stall Time Hot s										
		250) 50	00 1	000 2	000	4000	8000	Hz	Safe Stall Time Cold s										
S	PL@3								dB(A)	_ Frame material										
Mome	nt of iner	rtia					Lb-ft ²			Color, paint shade Standard Paint - RAL7030										
Ext Loa	ad Inertia	Capabilit	y:				Lb ft ²			Coating (paint finish) Standard Alkyed + Epoxy (C2)										
Bearin	-						1				ation Ty									
	g DE ND	DE								Method of cooling										
Bearin								Ball Bea	ring	Direction of rotation										
AFBMA										Fan Material										
Grease							1			VFD CT: VT:										
Capacity oz Grease Type:						oz Space heaters					-/- -/-									
Grease	Type:									Brake:										
Termi	nal box																			
	Lead Wire Connection Te								Termin	Terminal box position										
Volta	Voltage L1 L2 L3 Connected together							ether	Material of terminal box											
									Cable	entry					-	1-				
										-										
Notes:																				
$M_A/M_N = I$	ocked rotor t	rent / current torque / torqu corque / nomi	ue nominal								s valid only d power / at		ration with r	notor desi <u>c</u>	gn IC411					
Responsible department Technical reference Created by						Approved by Technical data are s				ubject to change! There may be discrepancies										
IN LV																				
Document type										Document status				custon	ner					
Datasheet										Released										
Document title												Document number								
1LE2221-1AA2				∿∠					Revision			on C	reation date	ate Language Pag			10			
© ABB 2024										01		2024-05-		-	1/					

			Main ter	minal diagram					
Transmittal reproduct	ion, dissemination and/or	editing of this document as well as	sutilization of its contents and cor	nmunication thereof to others with	hout expro	ss authorization	are prohibited. Offenders will	be held liable fo	r payment of
damages. All rights cre	ated by patent grant or re	editing of this document as well as gistration of a utility model or desi	ign patent are reserved.				promoteur orientiers Will		
Responsible depar	ment	Technical reference	Created by	Approved by	Technica be discre	ıl data are subj pancies betwe	ect to change! There may een calculated and rating	Link docum	ents
IN LVM				Created automatically	plate val	values.			
		Document type Wiring diagramm				Document status Released Document number			
		Document title							
		1LE2221-1AA2		WDS-240	0507-234135				
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-07	en	1/1