Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 1	45T - p	- 1.5 հր) -											
Client order no.							Item-No.						Offer no.						
Order no.						C	Consignment no.						Project						
Remarks										L									
F14	Electrical data																		
Electri	cai data	a																	
U A/Y f P P n				I Load	[Amps]		Nom. Eff Lo								T _A /T _N	T _k /T _N			
[V]	Δ/1	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
	T	1.457			T(NEVA			4.45
Frame Type: 145T					Type of constr.:								Motor Prot.:			NEMA			: 1.15
	Mtr. WT: II	bs	I	nsulation (sulation Class.:Standard Class F Insula				sulation Temp. R			e Cl.: B Amb. Temp.: + 40 to -20			1000 m	kV/	A:	IP 55	
Mech	anical d	lata																	
Sound	level (SP	L / SWL) a	it 60 Hz			dl	B(A) / dB	(A)		Thicke	ner								
	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Octave Band Center Frequencies Hertz								Safe Stall Time Hot					s	S				
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S		
S	PL@3								dB(A)	Frame material									
Mome	nt of ine	rtia					Lb-ft²			Color, paint shade Standard Paint - RAI						AL7030)		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)		
Bearin	igs						1			Ventilation Type									
Bearin	g DE NC	ÞΕ								Method of cooling									
Bearing	g_Type							Ball Bea	ring	Direction of rotation									
AFBM <i>A</i>	٨:									Fan Material									
Grease									VFD CT: VT:										
Capacity oz					oz		oz	Space heaters				-/-							
Grease Type:									Brake: -/-										
Termi	nal box	[
	Lead Wii	re Connec	tion							Termir	nal box p	osition							
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box									
										Cable entry -l-									
											,								
Notes:																			
$M_A/M_N = I$	ocked rotor	rrent / current torque / torqu	ue nominal								s valid only d power / at		eration with r	notor de	sign IC411				
M _v /M _n = break down torque / nominal torque Responsible department IN LVM Technical reference						Create	ed by		Approved by				Technical data are subject to change! Th				may be d	iscrepancies	
					Document type						Do			Document status c				er	
Datasheet												Released				custome			
Document title										Document number				1					
1LE2221-1AB3					3														
												on	Creation date	e	Languag	je Pag	je		
© ABB 2024											01		2024-05-	03 08:54	en	1/	1		

			Main te	rminal diagram					
				•					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	s utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	are prohibited. Offenders will	be held liable fo	r payment of
Responsible depar	tment	Technical reference	Created by	Approved by	be discre	ı data are subj pancies betwe	ect to change! There may en calculated and rating	Link docum	<u>ents</u>
IN LVM		Danima di	<u> </u>	Created automatically	plate valu			国意識	
	Document type Document status Wiring diagramm Released								
		Wiring diagramm Document title	Document	aumhar	3930 3800				
		1LE2221-1AB3					number 0503-085446		
Restricted		- ILEZZZ I- IAB3				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	en	1/1