Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 1	82T - p	- 1.5 հր	) -											
							Item-No.					Offer no.							
Order no.						(	Consignme	nt no.					Project						
Remarks																			
	Electrical data																		
Electri	cal data	3																	
U A/Y f P P				n		I Load	[Amps]	1		Nom. Eff Load [%]			2/4   4/4   2/4   2/4			.			
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Era	mo Typo:	102T			Type of	constr :							Motor Prot			NEMA	Dos	C F	. 1 15
Frame Type: 182T				Type of constr.:															
	Mtr. WT: II	bs	I	nsulation (	sulation Class.:Standard Class F Insulation				Temp. Rise Cl.: B			Amb. Temp.: + 40 to -20 °C @1000 m				kVA: IP 55			55
Mecha	anical d	lata																	
Sound	level (SP	L / SWL) a	it 60 Hz			dl	B(A) / dB	(A)		Thicke	ner								
				nd Cente	er Freque			` '			Safe Stall Time Hot s								
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold						S			
SI	PL@3								dB(A)	Frame material									
Mome	nt of ine	rtia					Lb-ft²			Color, paint shade Standard Paint - RAL70							L7030		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (Coating (paint finish)							oxy (C	2)	
Bearin	gs									Ventilation Type									
Bearing	g DE   NC	ÞΕ								Method of cooling									
Bearing	g_Type							Ball Bearing			Direction of rotation								
AFBMA	۸:									Fan Material									
Grease	2						,			VFD CT: VT:									
Capacity oz					oz		oz		Space heaters				-/-						
Grease Type:							·	Brake:				-/-							
Termi	nal box	[																	
	Lead Wii	re Connec	tion							Tormir	aal boy n	ocition							
Voltag	Voltage L1 L2 L3 Connected together								ether	Terminal box position  Material of terminal box									
	colocate together								Cable entry -/-										
										Cabic	citity					,			
										-									
Notes:																			
		rrent / current torque / torqu									s valid only d power / at		eration with r	notor de	sign IC411				
		torque / nomi									a povici / ac								
Responsible department Technical reference IN LVM					Create SPC	ed by		Approved by				Technical data are subject to change! There may be discre				screpancies			
Document type  Datasheet  Document title  1LE2221-1CC1										Do			Document status				r		
												Released							
											Document number								
				1															
												on	Creation date	e	Languag	e Pag	e		
© ABB 2024										01		2024-05-	06 18:40	en	1/1	l			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	ithout expres	s authorization	n are prohibited. Offenders will	l be held liable fo	r payment of
December 21 to the control of the co		IT. b. Callada	I constitution	I.a	T	I d-4		Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by	be discrep	i aata are subj pancies betwe ues.	ect to change! There may een calculated and rating	Link docum	<u>ents</u>
		Document type	<u> </u>	Created automatically		Document :	status	988	
Wiring diagramm Released									20.25
							number		
		1LE2221-1CC1			1		0506-184100		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-06	len	1/1