Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 2	15T - p	- 10 hp	-											
Client order no.							Item-No.						Offer no.						
Order no.						(Consignment no.						Project						
Remarks																			
F1	Electrical data																		
Electri	cal data	a																	
U A/Y f P P n				I Load	[Amps]		Nom. Eff Load								Torque T _A /T _N T _k /T				
[V]	Δ/1	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	RT [%]	BDT [%]
Frame Type: 215T Type of constr.:				constr.:				Motor P			Motor Prot	Prot.: NEMA [Des.: S.F.: 1.15				
	Mtr. WT: lbs			nsulation	nsulation Class.:Standard Class F Insulatio				Temp. F	Rise Cl.: B	Cl.: B Amb. Temp.: + 40 to -2			-20 °C @1000 m kVA:			: IP 55		
Mecha	anical d	lata																	
			nt 60 Hz			d	R(A) / dR	(A)		Thicke	ner								
Journa	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Octave Band Center Frequencies Hertz								Safe Stall Time Hot s										
		250				000	4000	8000	Hz		Safe Stall Time Cold						S		
S	PL@3								dB(A)	Frame material				-					
Mome	Moment of inertia Lb-ft²									Color, paint shade Standard Paint - RAL70						L7030			
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coatin	Coating (paint finish) Standard Alkyed + Epoxy (oxy (C2	2)	
Bearin	gs									Ventil	ation Ty	pe							
Bearing	g DE NC	DΕ								Method of cooling									
Bearing	g_Type							Ball Bea	ring	Direction of rotation									
AFBM <i>A</i>	AFBMA:								Fan Material										
Grease	2						ļ			VFD CT: VT:									
Capacity oz					OZ		OZ		Space heaters					-/-					
Grease Type:									Brake: -/-										
Termi	nal box	[
Lead Wire Connection Terminal box								nal box p	osition										
Volta	Voltage L1 L2 L3 Connected together								Material of terminal box										
									Cable	entry					-/-				
										_									
Notes:																			
		rrent / current torque / torqu									s valid only d power / at		eration with r	notor de	sign IC411				
		torque / nomi								2) at late	u power rat	ruii ioau							
1 1							Created by			Approved by			Technical data are subject to change! The				ay be dis	screpancies	
IN LVI	VI			SPC Document type									Document status customei						
Document type													Released						
Datasheet Document title 1LE2221-2AA2											Document number								
				\2															
									-			on	Creation date	e	Language	Page	e		
© ABB 2024									01 2024-05				2024-05-	04 <u>22</u> :18	en	1/1			

			Main te	rminal diagram					
Transmittal, reproduc	tion, dissemination and/or	r editing of this document as well a egistration of a utility model or des	s utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	are prohibited. Offenders will	be held liable for	r payment of
damages. All rights cr	eated by patent grant or re	egistration of a utility model of des	ign patent are reserved.						
Responsible depar	tment	Technical reference	Created by	Approved by	Technical be discrep	data are subj ancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM			<u> </u>	Created automatically	plate valu	ies.		■ ##	
	Document type Document status								
		Wiring diagramm		Released		(10)22 (10)22	聚赛		
		Document title 1LE2221-2AA2				Document			
Restricted					L	Revision	0504-221845 Creation date	Language	Page
© Innomotics	2024					AA	2024-05-04	en	1/1