Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor type: FS: 215T - p - 5 hp - Client order no. Item-No.								0,00											
Client order no.						tern-No.						Offer	Offer no.						
Order no.					(Consignment no.						Project							
Remarks																			
Electrical data																			
U	f	Р	Р	n		I Load	[Amps]			Nom	n. Eff Loa	d [%]	Pw	r. Factor Lo	ad [%]	Torque	T _A /T _N	T _k /T _N	
[V] Δ/Y	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: 215T Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.:	: 1.15		
Mtr. WT: lb	S	lı	Insulation Class.:Standard Class F				F Insulation Tem			Rise Cl.: B Amb. Temp.: + 40			0 to -20 °C @1000 m			kVA:		55	
Mechanical d	ata																		
Sound level (SPI	/ SWI) a	rt 60 Hz			Ч	B(A) / dB	:(A)		Thicke	ner									
Southa level (SI I			nd Cente	r Freque					Thickener Safe Stall Time Hot s										
	250				000	4000	8000	Hz	Safe Stall Time Cold s										
SPL@3								dB(A)	Frame material										
Moment of iner	Moment of inertia Lb-ft ²								Color, paint shade Standard Paint - RAL7030										
Ext Load Inertia	Ext Load Inertia Capability: Lb ft²								Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)			
Bearings									Ventilation Type										
Bearing DE ND	E								Method of cooling										
Bearing_Type Ball Bearing						ring	Direction of rotation												
AFBMA:								Fan Material											
Grease					VFD					CT: VT:									
Capacity oz				OZ		OZ		Space heaters					-/-						
Grease Type:								Brake:							-/-				
Terminal box																			
	e Connec	tion																	
	Lead Wire Connection							ether	Terminal box position Material of terminal box										
Voltage	Voltage L1 L2 L3 Connected together							etilei	Cable entry -/-										
									Cable	entry					-1-				
									-										
Notes:																			
I _A /I _N = locked rotor curi												eration with r	notor des	sign IC411					
$M_A/M_N = locked rotor t$ $M_K/M_N = break down to$									2) at rate	d power / at	full load								
Responsible depart	ment		Technic	cal referen	ce	Creat	ed by		Appr	oved by			Tech	nical data are s		nge! There n	nay be di:	screpancies	
IN LVM						SPC													
			Document type						Rele			cument status			custome	r			
Datasheet Document title 1LE2221-2AC2								Released				1							
											Document number								
				.2	•								on Creation date			Language Page			
© ABB 2024												Revisi 01		2024-05-0			1/1		
○ 1100 ZUZ⊤												101			11.03	U11			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorization	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discre	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Dogurt-t		Created automatically	plate valu		ctatus	具数	
Document type Document status Wiring diagramm Released									
		Document title		Document	number				
		1LE2221-2AC2					0502-110956		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-02	en	1/1