Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 2	86T - p	- 30 hp	-											
Client order no.						I	Item-No.						Offer no.						
Order no.						(Consignme	nt no.					Project						
Remarks																			
<u> </u>	Electrical data																		
Electri	cal data	3																	
			n		I Load [Amps]				Nom. Eff Load [%]			14 414 314 314			.		T _k /T _N		
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 286T Type of constr.:											Motor Prot			NEMA	Des :	S E -	: 1.15		
Frame Type: 286T				2.															
	Mtr. WT: II	bs		nsulation	sulation Class.:Standard Class F Insulatio				Temp. Rise Cl.: B			B Amb. Temp.: + 40 to -20 °C @1000 i				kVA: IP 54			954
Mecha	anical d	lata																	
Sound	Sound level (SPL / SWL) at 60 Hz																		
				ınd Cente	er Freque					Safe S	Safe Stall Time Hot s						s		
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold						S			
S	PL@3								dB(A)	Frame material									
Mome	nt of ine	rtia					Lb-ft²			Color, paint shade Standard Paint - RAL7						L7030			
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2							2)		
Bearin	ıgs									Ventilation Type									
Bearing	g DE NC	ÞΕ								Method of cooling									
Bearing	g_Type							Ball Bearing			Direction of rotation								
AFBM <i>A</i>	۸:									Fan Material									
Grease	e									VFD CT: VT:									
Capacity oz					oz		oz	Space heaters				-1-							
Grease Type:									Brake:				-1-						
Termi	nal box	[
	Lead Wir	re Connec	tion							Termir	nal hox n	osition							
Volta	Voltage L1 L2 L3 Connected together								ether	Terminal box position Material of terminal box									
	_								Cable entry -l-										
										-						,			
										_									
Notes:																			
		rrent / current torque / torqu									s valid only d power / at		eration with r	notor de	sign IC411				
		torque / nomi	nal torque	Tashni	cal referen		Croate	ıd bu		LAnne	oved by			Tech	nical data are	subject to cha	ngel There n	nav he di	iscrenancies
Responsible department Technical reference IN LVM					Le	Create SPC	u by		Appr	Approved by			Technical data are subject to change! There may be discre				screpuncies		
Document type Datasheet													Document status cus Released				r		
Document title 1LE2221-2CB2.												Document number							
				32											<u> </u>				
										F			on	Creation date		Languag	·		
© ABE	© ABB 2024												01		2024-05-	03 06:12	en	1/1	l

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	thout expres	ss authorizatior	are prohibited. Offenders will	be held liable fo	r payment of
December 21 to the control of the co		I To the Control of Control	I constitution	I.a	T	l d-4		Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by Created automatically	be discre plate valu	i aata are subj pancies betwe ues.	ect to change! There may en calculated and rating	Link docum	<u>ents</u>
		Document type	<u> </u>		1	Document :	status		
Wiring diagramm Released									20.25
		Document title	Document i	number					
		1LE2221-2CB2					0503-061302		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	len	1/1