Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 2	84TS -	p - 25 h	p -											
							tem-No.					Offer	Offer no.						
Order no.						(	Consignme	nt no.					Project						
							Consignment no.						9						
Remarks	Actildas																		
Electrical data																			
U Δ/Υ f P [Hz] [HI			P [HP]	P [kW]	n [rnm]		I Load [Amps]				Nom. Eff Load [%]			2/4   4/4   2/4   2/4			.		T <sub>k</sub> /T <sub>N</sub>
[v]		[П2]	[HF]	[KVV]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	+ 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 284TS Type of constr : Mo									Motor Prot			NEMA	Des :	S E -	· 1 15				
Frame Type: 284TS					Type of constr.:														
	Mtr. WT: II	bs	I	nsulation (	sulation Class.:Standard Class F Ins				Insulation Temp. R			se Cl.: B Amb. Temp.: + 40 to -20			1000 m	kVA	ν:	IP 54	
Mecha	anical d	lata																	
Sound	level (SP	L / SWL) a	at 60 Hz			d	B(A) / dB	(A)		Thicke	ner								
Journa	ievei (3i			nd Cente	er Freque			(11)		Safe Stall Time Hot s									
		250				000	4000	8000	Hz	Safe Stall Time Cold					s				
S	PL@3								dB(A)	Frame material									
Mome	Moment of inertia Lb-ft²									Color, paint shade Standard Paint - R.						Paint - RA	L7030		
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (						oxy (C	2)		
Bearin	ıgs									Ventil	ation Ty	pe							
Bearing	g DE   ND	ÞΕ								Method of cooling									
Bearing	g_Type							Ball Bea	ring	Direction of rotation									
AFBM <i>A</i>	۸:									Fan Material									
Grease	e						'							T: VT:					
Capacity oz					OZ		OZ		Space heaters					-1-					
Grease Type:									Brake:					-1-					
Termi	nal box	[																	
	Lead Wir	re Connec	ction							Termin	nal box p	osition							
Volta	Voltage L1 L2 L3 Connected together								Material of terminal box										
	5***								Cable entry -/-										
											,								
										-									
Notes:																			
I <sub>A</sub> /I <sub>N</sub> = lock	ked rotor cur	rrent / current											eration with r	notor de	esign IC411				
		torque / torqu torque / nomi								2) at rate	d power / at	full load							
Responsible department Technical reference					Create SPC	ed by		Approved by				Technical data are subject to char				nge! There may be discrepancies			
Document type Datasheet					ı				1			Document status				r			
												Rele	Released						
Document title 1LE2221-2DA1												Document number							
				\1											<u> </u>				
													Revisi	on	Creation dat		Languag	·	
© ARE	© ABB 2024												01		2024-05-	U3 U6:31	en	1/1	I

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorization	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discre	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Downstate		Created automaticall	plate valu	Document status		<b>国</b> (%)	
Document type  Wiring diagramm  Document status  Released									
		Document title		Document	number				
		1LE2221-2DA1					0503-063141		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	en	1/1