Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:				FS: 3	26T -	p - 25 hp	-												
Client order no.							Item-No.					Offer	Offer no.							
Order no.						Consignment no.					Proje	Project								
Remarks																				
F1																				
Electric	cal data																			
U		f	Р	P n I Load [Amps]					Nom. Eff Load [%]				Pwr. Factor Load [%] To				orque T _A /T _N T _k /T _N			
[V]	Δ/Υ	I [Hz]	(HP)	r [kW]	n [rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%		
		60	25.00	18.50																
Frame Type: 326T Type of constr.					constr.					Motor Prot.				.: NEMA [Des.: S.F.: 1.15			
Mtr. WT: lbs Insulation Class.:Standard Cla					ss F Insulatio	Rise Cl.: B	e Cl.: B Amb. Temp.: + 40 to -20 °				°C @1000 m kVA:			IP 54						
Mecha	nical d	ata																		
Sound	level (SPI	. / SWL) a	at 60 Hz				dB(A)/dB	(A)		Thicke	ner									
		C	octave Ba	nd Cente	er Freque	ncies H	ertz			Safe Stall Time Hot						s				
		250) 50	0 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S			
SI	SPL@3 dB(A)									Frame material										
Momer	nt of iner	ia					Lb-ft ²			Color, paint shade						Standard Paint - RAL7030				
	d Inertia	Capabilit	ty:				Lb ft ²			Coatin	ig (paint i	finish)			S	tandard A	kyed + E	роху (C2)	
Bearing	-						I				ation Ty									
	J DE ND	-								Method of cooling										
Bearing								Ball Bea	ring	Direction of rotation										
AFBMA										Fan Material VFD CT: VT:										
Grease Capacity oz							VFD oz Space heaters						- <i>I</i> -							
Grease						02	02			Brake:	Space heaters			-1-						
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,																			
Termi	nal box																			
Lead Wire Connection Terminal box position																				
Voltage L1 L2 L3 Connected together							Material of terminal box													
							Cable	entry					-1-							
										-										
Notes:																				
$M_A/M_N = 10$	ed rotor curr ocked rotor to reak down to	orque / torqu	ue nominal								s valid only d power / at :		ration with r	notor des	gn IC411					
Respons	sponsible department Technical reference Created by						Approved by				Technical data are subject to change! There may be discrepancies									
IN LVN	N LVM SPC							<u> </u>												
Document type												ment sta	tus		custom	ner				
Datasheet Document title 1LE2221-3AD2												Released Document number								
												Revisi	on	Creation dat	e	Langua	ige Pa	ige		
© ABB	© ABB 2024										01		2024-05-	02 18:45	en	1	/1			

			Main ter	minal diagram					
Transmittal, reproduct damages. All rights cre	ion, dissemination and/or ated by patent grant or re	editing of this document as well as gistration of a utility model or desi	utilization of its contents and con gn patent are reserved.	nmunication thereof to others with	hout expre	ess authorization	are prohibited. Offenders will	be held liable fo	r payment of
Responsible depar	ment	Technical reference	Created by	Approved by	Technico	al data are subi	ect to change! There may	Link docum	ents
IN LVM	ment		Created by	Created automatically	be discre	epancies betwe lues.	ect to change! There may en calculated and rating		<u>unto</u>
	Document type Document status								
		Wiring diagramm	Released						
	Document titleDocument number1LE2221-3AD2WDS-240502-184552								
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-02	en	1/1
						-		-	