Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor type: FS: 444TS - p - 125 hp - Client order no. Item-No.									04										
Client order no.						tern-ivo.						Offer	Offer no.						
Order no.					(Consignment no.						Project							
Remarks																			
Electrical da	ta																		
U	f	Р	Р	n		I Load	[Amps]			Non	n. Eff Loa	d [%]	lwl	. Factor Lo	ad [%]	Torque	T _A /T _N	T _k /T _N	
[V] Δ/Y	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: 444TS Type of constr.:							Motor Prot.: NEMA Des.:					S.F.	: 1.15						
Mtr. WT:	lbs	lı	nsulation (Class.:Stan	dard Clas	F Insulation Tem			Rise Cl.: B Amb. Temp.: + 4			+ 40 to -20	0 to -20 °C @1000 m			kVA: IP 54		954	
Mechanical																			
Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																			
	250		nd Cente	•	ncies He 000	rtz 4000	8000	Hz	Safe Stall Time Hot s										
SPL@3		, ,		_				dB(A)	Safe Stall Time Cold s										
						11. 6.2		(-)	Frame material										
Moment of inc		h.,				Lb-ft ² Lb ft ²			Color, paint shade Standard Paint - RAL7030										
Ext Load Inert	а Саравіііі	ıy:				LD IL-			Coating (paint finish) Standard Alkyed + Epoxy (C2)										
	Bearings								Ventilation Type Method of cooling										
Bearing DE NDE Bearing Type Ball Bearing							Direction of rotation												
Bearing_Type							ван веа	illig	Direction of rotation Fan Material										
	AFBMA:																		
Grease					1			VFD CT: VT:											
Capacity Grease Type:					OZ						pace heaters -/-								
drease Type.									Brake:										
Terminal bo	x																		
		rtion							- ·										
	Lead Wire Connection							ether	Terminal box position Material of terminal box										
voitage	Voltage L1 L2 L3 Connected together							etilei			ninal box	(,				
									Cable	entry					-/-				
									-										
Notes: I _A /I _N = locked rotor of	urrent / curren	t nominal							2) Value i	s valid only	for DOL on	eration with r	notor dos	ian IC411					
M _A /M _N = locked roto	r torque / torqu	ue nominal								s valid only d power / at		eration with r	notor des	ign IC411					
M _K /M _N = break dowi		inal torque	1			1_			1.				1- /						
Responsible dep	artment		Technic	cal referen	ce	Create SPC	ed by		Appr	oved by			Techi	nical data are s		nge! There i	may be d	screpancies	
IIN LVIVI			Document type									Docu	Document status customer			er			
													Released						
Datasheet Document title											Document number				1				
1LE2221-4DA1					A1														
			┪ ̄ ̄	. = .								Revisi	on	Creation date	9	Languag	ge Pag	je	
© ABB 2024												01		2024-05-0	06 09:44	en	1/	1	

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	ithout expres	s authorizatior	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Degument		Created automatically			ctatus	国次级	
	Document type Wiring diagramm Released								
		Document title		Document i	number	38 36 3 25 32 2			
		1LE2221-4DA1					0506-094429		
Restricted		1			L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-06	en	1/1