<u>Data</u>	sheet	t for th	iree-p	hase S	Squirro	el-Ca	ge-Mot	ors A	<u>BB</u>											
Motor	type:				FS: 4	44TS -	p - 125	1р -												
Client order no.						Item-No.					Offer	Offer no.								
Order no.							Consignment no.					Proje	Project							
Remarks																				
Electri	cal data																			
Liectri	cal uata	a																		
U AUX f P P n ILoa					l Load	I Load [Amps] Nom. Eff L					d [%]	Factor Lo	ad [%]	Torque	T <sub>A</sub> /T <sub>N</sub>	T <sub>k</sub> /T <sub>N</sub>				
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frar	ne Type: 4	144TS			Type of	constr.:							Motor Prot	.:		NEM	A Des.:	S.F.	: 1.15	
Mtr. WT: lbs Insulation Class.:Standard Clas				dard Cla	ss E Insulation Temp R			se Cl · B Amb Temp · + 40 t				to -20 °C @1000 m			kVA: IP		54			
		55		isuation	clusssturi		ss F Insulation Temp. Rise Cl.: B Ar				/ ///	b. remp.	1 10 10 20		00 m	K	kVA: IP 54			
Mecha	anical d	lata																		
Sound	lovol (SP	'L / SWL) a	at 60 Hz				B(A) / dB(	۵)		Thicke	ner									
Sound	ievei (SP			nd Cent	er Freque		B(A) / dB(	A)		Thickener										
		250				000	4000	8000	Hz	Safe Stall Time Hot s Safe Stall Time Cold s										
S	PL@3								dB(A)		Frame material				5					
Mome	nt of iner	rtia					Lb-ft <sup>2</sup>			Color, paint shade Standard Paint - RAL7030							)			
Ext Loa	nd Inertia	Capabilit	ty:				Lb ft²			Color, paint shade         Standard Paint - KE7050           Coating (paint finish)         Standard Alkyed + Epoxy (C2)										
Bearin	gs									Ventil	ation Ty	pe					-			
Bearing	g DE   ND	DE								Method of cooling										
Bearing	g_Type							Ball Bea	ring	Direction of rotation										
AFBMA	<b>\:</b>									Fan Material										
Grease	9						1			VFD CT: VT:										
Capacity oz						oz		Space	Space heaters					-/-						
Grease	Type:							Brake:	Brake:					-1-						
Termi	nal box	[																		
	Lead Wir	re Connec	tion							Termir	nal box po	osition								
Volta	Voltage L1 L2 L3 Connected together							ether	Material of terminal box											
								Cable entry -/-												
										_										
Notes:	rad rata: -:	rrent / curren	t nomin-l							2) 1/-1 '	valid!	for DOL -:	eration with r	notor d'	un ICA11					
$M_A/M_N = 10$	ocked rotor	torque / torqi torque / torqi torque / nomi	ue nominal								s valid only d power / at i		. auon with f	notor desig	pr 10+1 1					
Responsible department Technical reference Created by						Approved by			Technical data are subject to change! There may be discrepancies											
IN LVN	I LVM SPC										· ·	· ·								
Document type Datasheet Document title 1LE2221-4DA1										Docu	Document status				ner					
										Released										
											Document number									
											vision Creation date Land			Langu	age Pag	10				
© ABB 2024								Revision         Creation date         Lang           01         2024-05-05 15:10         en					-	1/*						

			Main ter	minal diagram					
Transmittal second in	on diccomination	aditing of this document	utilization of its contacts and	nmunication thereof to attack and	hout	cc authori+:	are prohibited Offerdare "	ho hold line (	or payment of
damages. All rights cre	ated by patent grant or re	editing of this document as well as gistration of a utility model or design	gn patent are reserved.	minumication thereof to others wit	nout expre	ss autriorization	are promoted. Offenders will	i ve neid liable f	or payment of
Responsible depart	ment	Technical reference	Created by	Approved by	Technica	ıl data are subj	ect to change! There may en calculated and rating	Link docun	<u>nents</u>
IN LVM				Created automatically	be discre plate val	pancies betwe ues.	en calculated and rating	同的	
		Document type			1	Document s	itatus		
	Wiring diagramm   Released								
		Document title				Document number WDS-240505-151018			
		1LE2221-4DA1							
Restricted © Innomotics	2024					Revision AA	Creation date 2024-05-05	Language	Page 1/1
	2024					<u>^</u>	2024-03-03	en	[ '''