<u>Data</u>	sheet	t for th	iree-p	hase S	Squirre	el-Cag	ge-Mot	ors A	<u>BB</u>										
Motor	type:				FS: 4	47TS -	p - 200	- מו											
Motor type: FS: 447TS Client order no.						Item-No.					Offer	Offer no.							
Order no.					(Consignment no.					Proje	Project							
Remarks	Remarks																		
-1																			
Electri	cal data	3																	
U f P P n I Load [Amps]							ff Load [%] Pwr. Factor Lo						T _k /T _N						
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Fran	me Type: 4	147TS			Type of	constr.:							Motor Prot	.:		NEM	A Des.:	S.F.	: 1.15
	Mtr. WT: ll	bs	h	Insulation Class.:Standard Class F Insulation Temp.						ise Cl.: B Amb. Temp.: + 40 to -20 °C @1000 m				k	kVA: IP 54		° 54		
Mecha	anical d	ata																	
		L / SWL) a	ot 60 Hz			h	B(A) / dB(A)		Thicke	ner								
Jouna	level (JI			nd Cente	er Freque			r,		-		Hot					s		
		250				000	4000	8000	Hz	Safe Stall Time Hot s Safe Stall Time Cold s									
S	PL@3								dB(A)		Frame material								
Mome	nt of iner	rtia					Lb-ft ²			Color, paint shade Standard Paint - RAL7030)		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)								2)	
Bearin	gs									Ventilation Type									
Bearing	g DE ND	θE								Method of cooling									
Bearing	g_Type							Ball Bea	ring	Direction of rotation									
AFBMA	۸:									Fan Material									
Grease	9									VFD CT: VT:									
Capaci	ty					oz		oz Space heaters									-/-		
Grease	Type:									Brake: -/-									
Tormi	nal box																		
		re Connec		10			Conno	ctod tog	othor	Terminal box position									
Voltage L1 L2 L3 Connected together						ether	Material of terminal box Cable entry -/-												
								Cable	entry					-	-				
										-									
Notes:	ad r-t-	ront I	nortin 1							3) 16.1	التامير م	for DOI	vatio'.!	note - 1	an IC411				
$M_A/M_N = I_0$	ocked rotor	rent / current torque / torqu :orque / nomi	ue nominal								s valid only d power / at		ration with r	notor desig	jiri⊂411				
M _d /M _n = break down torque / nominal torque Responsible department Technical reference Created by					Approved by Te				Techni	Technical data are subject to change! There may be discrepancies									
	IN LVM SPC								1.										
Document type							1			Docu	Document status customer				ner				
Datasheet Document title 1LE2221-4DB3										Released									
											Document number								
				33															
© ABB 2024											Revisi		reation date		Langua 7 en	age Pag			

		Mai	n terminal diagram					
and the t	p - 1 - 11 - 112					1111-1-4-22		
I ransmittal, reproduction damages. All rights creat	n, dissemination and/or editing of this docum ed by patent grant or registration of a utility	ent as well as utilization of its contents a model or design patent are reserved.	and communication thereof to others wi	thout expre	ess authorizatior	are prohibited. Offenders wil	I be held liable f	or payment of
Responsible departm	ent Technical refere	nce Created by	Approved by	Technico	al data are subi	ect to change! There may	Link docun	ients
IN LVM			Created automatically	be discre plate va	epancies betwe lues.	ect to change! There may een calculated and rating		
	Document type	I		1	Document status			
	Wiring diagramm Released							
	Document title				Document number			
	1LE2221-4D)B3				0503-210724		
Restricted	024				Revision	Creation date	Language	Page
© Innomotics 2	UZ4				AA	2024-05-03	en	1/1