Consideration Consideratio	Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Contact of the Cont	Motor	type:				FS: 4	44TS -	p - 100	hp -											
	Client order no.													Offer no.						
	Order no.						(Consignme	nt no.					Proje	ct					
D	Remarks																			
D																				
1	Electri	cal data	1																	
Traine Type 44475						1	1	1 _	4/4 3/4				l		214					
Mechanical data Mechanical data Sound level (SPL/ SWL) at 60 Hz Octave Band Center Frequencies Herz 250 500 1000 2000 4000 8000 Hz SST-833 ddt(A) Moment of inertia LD-ft' Coolor, paint shade Searing, Dye Bearing DE NDE Bearing, Dye Bearing DE NDE NDE NDE Bearing DE NDE	[1		[112]	[,,,,]	[KW]	[ipiii]	4/4	3/4	1/2	0	LRC	7/4	314	214	4/-	314	214	[lb-ft]	LRT [%]	BDT [%]
Mechanical data Mechanical data Sound level (SPL/ SWL) at 60 Hz Octave Band Center Frequencies Herz 250 500 1000 2000 4000 8000 Hz SST-833 ddt(A) Moment of inertia LD-ft' Coolor, paint shade Searing, Dye Bearing DE NDE Bearing, Dye Bearing DE NDE NDE NDE Bearing DE NDE	Fran	ne Type: 4	44TS			Type of	constr.:							Motor Prot			NEMA	Des :	S.F.	· 1 15
Mechanical data Sound level (SPL / SWL) at 60 Hz Octave Band Center Frequencies Hersz 250 500 1000 2000 4000 8000 Hz SPL@3 500 1000 2000 4000 8000 Hz SPL@3 565 101 Time Cold 5 Ext Load Inertia Capability: Lb ft² Coding (paint finish) Standard Paint - RAL7030 Bearings Ext Load Inertia Capability: Lb ft² Coding (paint finish) Standard Alkyed + Epoxy (C2) Westillation Type Bearing_Type Bearing_Type Bearing_Type Ball Bearing Direction of rotation Freake Fan Material FPD CT: VT: FPD CT: VT: Freminal box Lead Wire Connection Voltage L1 L2 L3 Connected together Terminal box Lieud Wire Connection Voltage L1 L2 L3 Connected together Terminal box Cable entry Above: Lieud Wire Connection Terminal box Cable entry Above: Direction Connected together Terminal box Cable entry Above: Direction Connected together Terminal box Cable entry Above: Direction Capability Terminal box Cable entry Above: Direction Connected together Direction Connected together Direction Connected together Terminal box Cable entry Above: Direction date are analysed to disregard Fixes way be disrepanced Direction Connected together Direc								- F ll-4:		T [Ninn Cl i D									
Source Sept		Mtr. WI: I	OS		nsulation	Class.:Stan	dard Class	Class F Insulation Temp.				Cl.: B Amb. Temp.: + 40 to -20 °C @				1000 m	KVF	IP	54	
Octave Band Center Frequencies Herz 250	Mecha	nical d	ata																	
Cotave Band Center Frequencies Hertz 250 500 1000 2000 4000 4000 8000 Hz 256 Sall Time Cold 5 sets Sal	Sound	level (SP	L / SWL) a	it 60 Hz			dl	3(A) / dB	(A)		Thicke	ner								
SPLEAS ABOUT THE Color Service												Hot					s			
Moment of inertia			250	50	00 10	000 2	000	4000	8000	Hz							S			
Ext Load Inertia Capability: Lb ft* Coating (paint finish) Standard Alkyed + Epoxy (C2) Bearings Ventilation Type Method of cooling Ball Bearing Presented Coping AFBMA: Ball Bearing Fan Material Capacity	SI	PL@3								dB(A)										
Bearing S Ventilation Type Method of cooling Bearing DE I NDE Method of cooling Bearing Type Ball Bearing Direction of rotation AFBMA:	Mome	nt of iner	tia					Lb-ft²									L7030			
Bearing DE NDE Bearing_Type	Ext Loa	d Inertia	Capabilit	y:				Lb ft²										2)		
Bearing_Type Ball Bearing Fan Material Fan Material VFD CT: VT: Grease Capacity OZ OZ Space heaters	Bearin	gs									Ventil	ation Ty	pe							
AFBMA:	Bearing	DE ND	E																	
Grease Capacity oz oz Space heaters	Bearing	g_Type							Ball Bea	ring	Direction of rotation									
Greaze Type: Brake:	AFBMA	ι:									Fan Material									
Ferminal box Lead Wire Connection Voltage L1 L2 L3 Connected together Notes: Voltage L1 L2 L3 Connected together September 1 L4 L4 L5 L5 Connected together Notes: Voltage L1 L5 L5 Connected together September 1 L4 L5 L5 Connected together September 2 L5 L5 Connected together September 2 L5 L5 Connected together September 3 Sydule is valid only for DOL operation with motor design K411 2) at rated goover at full load Note: September 3 Sydule is valid only for DOL operation with motor design K411 2) at rated goover at full load Note: September 3 Sydule is valid only for DOL operation with motor design K411 2) at rated goover at full load Note: September 3 Sydule is valid only for DOL operation with motor design K411 2) at rated goover at full load Note: September 4 Staff load Document staffus September 5 Document staffus Customer 5 Document title 1 LE2221-4DC1 Revision Creation date Language Rage	Grease)																		
Ferminal box Lead Wire Connection Voltage L1 L2 L3 Connected together Notes:							oz		oz							-/-				
Notes: Notes:	Grease Type:									·										
Notes: Notes:																				
Notes: Notes:	Termi	nal box																		
Notes: Material of terminal box Cable entry		Lead Wir	e Connec	tion							Termir	nal box p	osition							
Notes: Julia Elocked rotor current / current nominal 3) Value is valid only for DOL operation with motor design IC411 Mulia Elocked rotor torque / torque nominal 2) at rated power / at full load Mulia Elocked rotor torque / nominal torque no	Voltag	Voltage L1 L2 L3 Connected together								ether										
Jan Socked rotor current / current nominal 2) value is valid only for DOL operation with motor design IC411 2) at rated power / at full load 2) at											Cable entry -/-									
Jan Socked rotor current / current nominal 2) value is valid only for DOL operation with motor design IC411 2) at rated power / at full load 2) at												,								
											-									
M _M /M _n = locked rotor torque / torque nominal M _M /M _n = break down torque / nominal torque Responsible department IN LVM Technical reference Created by SPC SPC		ed rotor cur	rent / current	nominal							3) Value i	s valid only	for DOL on	eration with r	notor de	sian IC411				
Responsible department IN LVM Technical reference Created by SPC Approved by Document type Datasheet Document title 1LE2221-4DC1 Revision Technical data are subject to change! There may be discrepancies Released Document number Revision Creation date Language Page	$M_A/M_N = 10$	ocked rotor t	torque / torqu	ue nominal										eration with	notor de	sigiric+rr				
Document type Datasheet Document title 1LE2221-4DC1 Revision Creation date Language Page	Responsible department Technical reference Created by							Approved by						ge! There may be discrepancies ·						
Datasheet Document title 1LE2221-4DC1 Revision Creation date Language Page											-									
Document title 1LE2221-4DC1 Revision Creation date Language Page																		r		
1LE2221-4DC1 Revision Creation date Language Page														4						
Revision Creation date Language Page						-1							Document number							
					-	∠∠1-4D(.1								Revision Creation date			1	anguage Page	
	© ARR	2024																1		

			Main te	rminal diagram							
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or reated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	ithout expres	s authorizatior	n are prohibited. Offenders will	be held liable for	r payment of		
Responsible depar	rtment	Technical reference	Created by	Approved by	be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>		
IN LVM		Document type		Created automatically			ctatus				
		Document type Wiring diagramm				Document :	ocatus				
		Document title			1	Document	number				
		1LE2221-4DC1			I		0504-212451				
Restricted		1			L	Revision	Creation date	Language	Page		
© Innomotics	2024					AA	2024-05-04	en	1/1		