Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 4	45TS -	p - 125	hp -											
							Item-No.					Offer	Offer no.						
Order no.						(Consignme	nt no.					Project						
													Tojett						
Remarks	VEIII (IA)																		
Electri	cal data	a																	
U D/Y f P			Р	n		I Load	[Amps]	ı		Nom. Eff Load [%]			14 414 314 314			.		T _k /T _N	
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 445TS Type of cor				constr.:		Motor Pr			Motor Prot										
Mtr. WT: lbs			I	Insulation Class.:Standard Class F Ir				Insulation Temp. R			e Cl.: B Amb. Temp.: + 40 to -2			-20 °C @1000 m kVA			: IP 54		
Mech:	Mechanical data																		
Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Octave Band Center Frequencies Hertz Safe Stall Time Hot s																			
		250				ncies He 000	4000	8000	Hz	Safe Stall Time Hot					S				
S	PL@3								dB(A)	Safe Stall Time Cold				\$					
Mome	nt of iner	rtia					Lb-ft²			Frame material Color, paint shade Standard Pa						Paint - RA	aint DAL7020		
		Capabilit	tv:				Lb ft²												
Bearin			,							Coating (paint finish) Standard Alkyed + Epoxy (C2) Ventilation Type								_,	
	g DE ND	ÞΕ								Method of cooling									
								Ball Bea	ring	Direction of rotation									
AFBM <i>A</i>								3	Fan Material										
Grease										VFD						C	T: VT:		
					OZ		oz		Space heaters				-1-						
Grease Type:								Brake:				-I-							
Termi	nal box	•																	
	Lead Wir	re Connec	ction							Termin	nal hov n	osition							
Volta	Voltage L1 L2 L3 Connected together								ether	Terminal box position Material of terminal box									
									Cable entry -/-										
									cabic						,				
										-									
Notes:																			
		rent / current											eration with r	notor de	sign IC411				
		torque / torqu corque / nomi								∠) at rate	d power / at	ruii ioad							
Responsible department Technical reference					Created by SPC			Approved by				Technical data are subject to change! There may be discrepand to the discrepand to t				screpancies			
IN LVM																			
Document type Datasheet Document title 1LE2221-4DC2												Document status				r			
											Released			-					
												Document number							
				.ZZZ 1-4DCZ									on	Creation date	e	Languag	e Page	e	
© ABB 2024														2024-05-			1/1		

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	thout expres	s authorizatior	n are prohibited. Offenders will	l be held liable fo	r payment of
December 21 to the control of the co		IT. b. Callada	I constitution	I.a	T	-d-4		Treatment	
Responsible depar	ument	Technical reference	Created by	Approved by Created automatically	be discrep plate valu	uata are subj pancies betwe ies.	ect to change! There may een calculated and rating	Link docume	ents
		Document type		Created automatically		Document :	status		
	Wiring diagramm Released Document title Document number								20.25
		1LE2221-4DC2				WDS-240	0504-050608	回機器	
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-04	len	1/1