Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor type: FS: 145T - p - 2 hp -																				
Client order no. Item-No.							tem-No.	<u> </u>					Offer	Offer no.						
Order no.						(Consignment no.						Project							
Remarks																				
Electri	Electrical data																			
Electri	cai uata	1																		
U A/Y fuel fuel feet feet			n I Load [Am						Nom. Eff Load [%]						.		T _k /T _N			
[V]	471	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
F	T	1457			Tues of								N4			NEMA			4.45	
Frame Type: 145T Type of constr.:									Motor Prof											
	Mtr. WT: II	bs	I	nsulation (lation Class.:Standard Class F Insulation				Temp. Rise Cl.: B Amb. Te			ıb. Temp.:	emp.: + 40 to -20 °C @1000 m				kVA: IP 55			
Mecha	Mechanical data																			
Sound	level (SP	L / SWL) a	ıt 60 Hz			dl	B(A) / dB	(A)		Thicke	ner									
	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Octave Band Center Frequencies Hertz										tall Time	Hot					s			
		250					4000	8000	Hz	Safe Stall Time Cold						S				
S	PL@3								dB(A)	Frame material										
Mome	Moment of inertia Lb-ft ²									Color,	Color, paint shade Standard Paint - RAL						L7030			
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coatin	g (paint	finish)								
Bearin	ıgs									Ventil	ation Ty	pe								
Bearing	g DE NC	ÞΕ								Method of cooling										
Bearing	g_Type							Ball Bea	ring	Direction of rotation										
AFBM <i>A</i>	۸:									Fan Material										
Grease	e									VFD CT: VT:										
Capaci	ty					oz		oz		Space heaters				-/-						
Grease Type:									Brake:	Brake:					-/-					
Termi	nal box	,																		
									Terminal box position											
Voita	Voltage L1 L2 L3 Connected together								Material of terminal box Cable entry -/-											
										Cable	entry					-/-				
<u> </u>																				
Notes: I _A /I _N = lock		rrent / current	nominal							3) Value i	s valid only	for DOL ope	eration with r	notor de	sign IC411					
		torque / torqu torque / nomi								2) at rate	d power / at	full load								
Responsible department Technical reference					Created by			Approved by				Technical data are subject to char				nge! There may be discrepancies				
				Document type							Do			Document status				r		
Datasheet											Released									
Document title 1LE2321-1AA3										Document number										
				١3																
												on	Creation date	e	Languag	e Pag	e			
© ABB 2024										01		2024-05-	03 23:01	en	1/1	1				

			Main te	rminal diagram					
Transmittal, reproduc	tion, dissemination and/or	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co	mmunication thereof to others wit	thout expres	ss authorization	are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	tment	Technical reference	Created by	Approved by	Technical be discre	l data are subj pancies betwe	ect to change! There may en calculated and rating	Link docume	<u>ents</u>
IN LVM		Designation		Created automatically	plate valu	ues.		回38	
	Document type Document status Wiring diagramm Released								
		Wiring diagramm Document title		Document	number	1930			
		1LE2321-1AA3					0503-230127		
Restricted		-				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	en	1/1