Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor type: FS: 145T - p - 1 hp -																			
							Item-No.					Offer	Offer no.						
Order no.						C	Consignme	nt no.					Project						
Remarks																			
Electri	Electrical data																		
Electri	Cai uala	1																	
U A/Y f P P			n		I Load [Amps]				Nom. Eff Load [%]						.		T _k /T _N		
[V]	471	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
		1.457			T(NEMA			4.45
Frame Type: 145T Type of constr.									Motor Prot										
	Mtr. WT: II	bs	I	nsulation (sulation Class.:Standard Class F Insula				sulation Temp. Ri			e Cl.: B Amb. Temp.: + 40 to -2			1000 m	kVA	: IP 55		
Mechanical data																			
Sound	level (SP	L / SWL) a	ıt 60 Hz			dl	B(A) / dB	(A)		Thicke	ner								
				nd Cente	er Freque			. ,			tall Time	Hot					S		
		250	50	00 10	000 2	000	4000	8000	Hz	Safe S	Safe Stall Time Cold						s		
S	PL@3								dB(A)	Frame material									
Mome	Moment of inertia Lb-ft ²								Color,	Color, paint shade Standard Paint - RAL						L7030			
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coatin	rting (paint finish) Standard Alkyed + Epoxy (C2)							2)	
Bearin	gs									Ventil	ation Ty	pe							
Bearing	g DE NC	ÞΕ								Method of cooling									
Bearing	g_Type							Ball Bea	ring	Direction of rotation									
AFBM <i>A</i>	۸:									Fan Material									
Grease	e									VFD CT: VT:									
Capacity oz						oz		oz		Space heaters					-/-				
Grease Type:									Brake: -/-					-/-					
Tormi	nal box	,																	
Termi																			
Valta	Lead Wire Connection								Terminal box position										
Voita	Voltage L1 L2 L3 Connected together								Material of terminal box Cable entry -l-										
									Cable	entry					-/-				
										-									
Notes:																			
$M_A/M_N = I$	ocked rotor	rrent / current torque / torqu torque / nomi	ue nominal								s valid only d power / at		eration with r	notor de	sign iC411				
M _e /M _N = break down torque / nominal torque Responsible department IN LVM Technical reference						Create	ed by		Approved by				Technical data are subject to char				nge! There may be discrepancies		
Document type							<u> </u>			Document status				custome	r				
Datasheet												Released							
Document title											Document number				1				
1LE2321-1AC3					3														
												Revisi	on	Creation date	e	Languag	e Pag	e	
© ABB 2024											01		2024-05-	02 18:59	en	1/1	l		

			Main te	minal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co- sign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	be discrep	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM				Created automatically	plate valu	ies.		□ 388	
	Document type Document status								
		Wiring diagramm		Released		- P	變寒		
		Document title				Document			
Doct-riet1		1LE2321-1AC3				Revision	0502-185942	Language	I Page
Restricted © Innomotics	2024					AA	Creation date 2024-05-02	Language en	Page 1/1