<u>Data</u>	sheet	for th	iree-p	hase	Squirro	el-Ca	ge-Mo	tors A	BB										
Motor	type:				FS: 1	82T - p	o - 1.5 hp) -											
Client order no.							Item-No.					Offer	Offer no.						
Order no.							Consignment no.					Proje	ct						
Remarks																			
Electri	cal data																		
U AVV f P P n					I Load	[Amps]		Nom. Eff Load [%]				Pwr. Factor Load [%]				Torque T _A /T _N T _k /T _N			
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Fra	ime Type: '	82T			Type of	constr.:						I	Motor Prot	.:		NEM	A Des.:	S.F.	: 1.15
	Mtr. WT: lk	s	1	nsulation	Class.:Stan	dard Clas	ss F Insulation Temp. Ri			ise Cl.: B	e Cl.: B Amh Temp · ± 40 to 20				0 °C @1000 m kV			A: IP 55	
		5			classifistari		ss Finsulation Temp. Rise				se Cl.: B Amb. Temp.: + 40 to -20 °C @1000 m					KVA. IF 55			55
Mech	anical d	ata																	
Sound	level (SP	/SWL) a	t 60 Hz			d	B(A)/dB	(A)		Thicke	ner								
Jound				nd Cente	er Freque			,,,,		Thickener 									
		250				000	4000	8000	Hz	Safe Stall Time Hot s Safe Stall Time Cold s									
S	PL@3								dB(A)	Frame material									
Mome	nt of iner	tia					Lb-ft ²			Color, paint shade Standard Paint - RAL7030)		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft ²			Coating (paint finish) Standard Alkyed + Epoxy (C2)								2)	
Bearin	gs										ation Ty								
Bearin	g DE ND	E									d of cool								
Bearin	g_Type							Ball Bea	ring	Direction of rotation									
AFBMA	٨:									Fan Material									
Grease	е									VFD CT: VT:									
Capaci	ty					oz		oz		Space heaters				-1-					
Grease	Type:									Brake:					-1-				
Termi	nal box																		
Lead Wire Connection Terminal box position																			
Voltage L1 L2 L3 Connected together							ether	Material of terminal box											
									Cable entry -/-										
										-									
Notes:										2)									
$M_A/M_N = I$	ked rotor cur ocked rotor t oreak down t	orque / torqu	ie nominal								s valid only d power / at f		ration with r	notor desi <u>o</u>	gn IC411				
Responsible department Technical reference Created by							Approved by			Technical data are subject to change! There may be discrepancies									
IN LVN									. 										
Document type					<u> </u>				Docum			ment status			custon	ner			
Datasheet Document title										Released Document number									
]					
1LE2321-1CC1				21															
© ABB 2024											Revisi		reation date		Langua 1 en	age Pag			

			Main te	rminal diagram					
,]	
Transmittal, reproduct damages. All rights cre	ion, dissemination and/or eated by patent grant or re	editing of this document as well as egistration of a utility model or desi	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	hout expre	ss authorizatior	are prohibited. Offenders will	be held liable fo	r payment of
Responsible depar IN LVM	iment	Technical reference	Created by	Approved by Created automatically	Technica be discre plate val	u aata are subj epancies betwe lues.	ect to change! There may en calculated and rating	Link docum	<u>ents</u>
		Document type		Created automatically	piate val		tatus		
	Document type Document status Wiring diagramm Released								
	Document title Document number								
		1LE2321-1CC1				WDS-240506-075134			和学校
Restricted				Revision Creation date Langua			Page		
© Innomotics	2024					AA	2024-05-06	en	1/1
		Į				I		I	ļ