<u>Data</u>	sheet	t for th	iree-p	hase S	Squirro	el-Ca	ge-Mot	ors A	<u>BB</u>											
Motor	type:				FS: 2	13T - p	o - 7.5 hp) -												
Client order no.							Item-No.						Offer	Offer no.						
Order no.							Consignment no.					Proje	Project							
Remarks	Remarks																			
Electri	cal data	•																		
U	U A LX f P P n I Load [Amps					[Amps]	Nom. Eff L			. Eff Loa	Load [%] Pwr. Factor Load] Torque T _A /T _N		T _k /T _N			
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Fra	me Type:	213T			Type of	constr.:							Motor Prot	.:		NEM	A Des.:	S.F.	: 1.15	
Mtr. WT: lbs Insulation Class.:Standard Cla				dard Clas	ss F Insulation Temp. F			se Cl.: B Amb. Temp · + 40 tr				to -20 °C @1000 m			kVA:		IP 55			
							ass F Insulation Temp. Rise Cl.: B				: B Amb. Temp.: + 40 to -20 °C @1000 m					KV/. IF 55			55	
Mecha	anical d	lata																		
Sound	level (SP	'L / SWL) a	at 60 Hz			d	B(A)/ dB(A)		Thicke	ner									
Jound	16461 (31			nd Cente	er Freque							Hot					s			
		250				000	4000	8000	Hz	Safe Stall Time Hot s Safe Stall Time Cold s										
S	PL@3								dB(A)		Frame material									
Mome	nt of iner	rtia					Lb-ft²			Color, paint shade Standard Paint - RAL7030										
Ext Loa	d Inertia	ı Capabilit	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)								2)		
Bearin	gs									Ventil	ation Ty	pe								
Bearing	g DE NC	DE								Method of cooling										
Bearing	g_Type							Ball Bea	ring	Direction of rotation										
AFBMA	:									Fan Material										
Grease	•									VFD CT: VT:										
Capacity oz						oz Space heaters					-1-									
Grease	Type:									Brake:	Brake: -/-									
Termi	nal box	[
	Lead Wii	re Connec	ction							Termir	nal box po	osition								
Voltag	ge	L1		L2	L	3	Conne	cted tog	ether	Material of terminal box										
								Cable entry -/-												
										-										
Notes:																				
$M_A/M_N = 10$	ocked rotor	rrent / curren torque / torqu	ue nominal								s valid only d power / at f		eration with r	notor desig	jn IC411					
		torque / nomi	mai torque	Techni	cal referen	ce	Create	d by		Annr	oved by			Techni	cal data are	subject to r	hange! Ther	e mav be di	iscrepancies	
IN LVN						, , , , , , , , , , , , , , , , , , , ,	y			1				, u						
Document type							Document status					custon	ner							
Datasheet Document title											Released Document number									
1LE2321-2AA1																				
© ABB 2024											Revisi 01		reation date		Langua 1 en	age Pag				

[Main ter	minal diagram					
l									
Transmittal reproduct	on, dissemination and/or	editing of this document as well as	utilization of its contents and cor	nmunication thereof to others with	hout expro	ss authorization	are prohibited. Offenders will	be held liable f	or payment of
damages. All rights cre	ated by patent grant or re	editing of this document as well as gistration of a utility model or design	gn patent are reserved.		uu expre	ss aathonzation	are promoted, orienders Will	Se neiù idule l	o, payment of
Responsible depart	ment	Technical reference	Created by	Approved by	Technica	l data are subj	ect to change! There may en calculated and rating	Link docun	nents
IN LVM				Created automatically	be discre plate val	pancies betwe ues.	en calculated and rating	同火的	
		Document type				Document status			
	Wiring diagramm Released								
		Document title				Document number WDS-240506-083114			
		1LE2321-2AA1							
Restricted © Innomotics	2024					Revision AA	Creation date 2024-05-06	Language en	Page 1/1
	2027	!					2027-03-00		1'''