Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	r type:				FS: 2	13T - p	- 3 hp -												
Client order no.							Item-No.						Offer no.						
Order no.						(Consignment no.						Project						
Remarks	Remarks																		
Flectri	cal data																		
Liectii	cai uate																		
U D/Y F P			Р	n		I Load [Amps]				Nom. Eff Load [%]			14 414 314 314			.		T _k /T _N	
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	4 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Fra	ıme Tyne:	213T			Type of	constr :							Motor Prot			NEMA	Des :	S E -	. 1 15
Frame Type: 213T			Type of constr.:						2: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5: 5:			Motor Prot.: mp.: + 40 to -20 °C @1000 m					S.F.: 1.15		
	Mtr. WT: II	DS		nsulation (ulation Class.:Standard Class F Insulation				Temp. F	Temp. Rise Cl.: B Amb. Tem			+ 40 to -20) ~ (@	1000 m	KV <i>F</i>	kVA: IP 55		
Mecha	anical d	lata																	
Sound	level (SP	L / SWL) a	ıt 60 Hz			dl	B(A) / dB	(A)		Thicke	ner								
		C	ctave Ba	nd Cente	er Freque	ncies He	rtz			Safe S	Safe Stall Time Hot s						S		
		250	50	0 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold						S			
S	PL@3								dB(A)	Frame material									
Mome	nt of ine	rtia					Lb-ft²			Color, paint shade Standard Paint - F						Paint - RA	L7030		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)		
Bearin	igs									Ventilation Type									
Bearing	g DE NC	ÞΕ								Method of cooling									
Bearing	g_Type							Ball Bearing Direction			ion of rot	ation							
AFBM <i>A</i>	٨:									Fan Material									
Grease									VFD CT: VT:										
Capacity oz					OZ		OZ	Space heaters				-/-							
Grease	Grease Type:									Brake: -/-									
Termi	nal box																		
	Lead Wii	re Connec	tion							Termin	nal box p	osition							
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box									
										Cable entry -l-									
Notes:																			
$M_A/M_N = I$	ocked rotor	rrent / current torque / torqu torque / nomi	ue nominal								s valid only d power / at		eration with r	notor de	esign IC411				
M _e /M _N = break down torque / nominal torque Responsible department IN LVM Technical reference						Create SPC	d by		Appr	Approved by			Technical data are subject to chan				nge! There may be discrepancies		
				Occument type						Doo			Document status				r		
Datasheet													Released						
Document title 1LE2321-2AC1												Document number							
				1															
												on	Creation dat		Languag	1			
© ABE	© ABB 2024												01		2024-05-	07 02:33	en	1/1	

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout expres	ss authorization	n are prohibited. Offenders will	l be held liable fo	r payment of
D 'I I I		I To the Control of Control	I constitution	I.a	T	l d-4		Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by	be discre plate valu	i aata are subj pancies betwe ues.	ect to change! There may een calculated and rating	Link docum	<u>ents</u>
		Document type	1	Created automatically	1	Document:	status		
Wiring diagramm Released								###()	20.25
		Document title	Document	number					
		1LE2321-2AC1					0507-023342		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-07	len	1/1