Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 2	84T - p	- 25 hp	-											
Client order no.						I	Item-No.						Offer no.						
Order no.						(Consignme	nt no.					Project						
Remarks																			
	Electrical data																		
Electri	cal data	3																	
			n			[Amps]			Nom. Eff Load [%			%] Pwr. Factor Load [%] 2/4 4/4 3/4 2/4			.	T _A /T _N	T _k /T _N		
[v]		[HZ]	[HP]	[KVV]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	1 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 284T Type of constr.:											Motor Prot			NEMA	Des :	S E -	· 1 15		
Frame Type: 284T																S.F.: 1.15			
	Mtr. WT: II	bs		nsulation	sulation Class.:Standard Class F Insulation				Temp. Rise Cl.: B Amb. Ter			ıb. Temp.:	+ 40 to -20		1000 m	kVA	kVA: IP 55		
Mecha	anical d	lata																	
Sound	level (SP	L / SWL) a	ıt 60 Hz			d	B(A) / dB	(A)		Thicke	ner								
		C	ctave Ba	ınd Cente	er Freque	ncies He	ertz			Safe Stall Time Hot s									
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold					S				
SI	PL@3								dB(A)	Frame material									
Mome	nt of ine	rtia					Lb-ft²			Color, paint shade Standard Paint - RAL70							L7030		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)		
Bearin	ıgs									Ventilation Type									
Bearing	g DE ND	ÞΕ								Method of cooling									
Bearing_Type Bal							Ball Bea	Ball Bearing Direction of rot			ation								
AFBMA	۸:									Fan Material									
Grease	e									VFD CT: VT:									
Capacity oz					oz		oz	Space heaters				-I-							
Grease Type:							Br				Brake:								
Termi	nal box	[
	Lead Wii	re Connec	tion							Termir	nal box p	osition							
Voltag	Voltage L1 L2 L3 Connected together								ether	Material of terminal box									
									Cable entry -/-										
										-									
Notes:																			
		rrent / current											eration with r	notor de	sign IC411				
		torque / torqu torque / nomi								2) at rate	d power / at	ruii ioad							
Responsible department Technical reference IN LVM					Create SPC	ed by		Approved by				Technical data are subject to change! Th				nay be di	iscrepancies		
-				Docum	Document type						Do			Document status				r	
Datasheet													Released						
Document title 1LE2321-2CB1										Document number				1					
				1															
									ľ			on	Creation dat	e	Languag	e Pag	e		
© ABB 2024										01		2024-05-	02 15:10	en	1/1	l			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	tment	Technical reference	Created by	Approved by	Technical be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Designation		Created automatically	plate valu	ies.		国 统数	
Document type Wiring diagramm Released Document title Document number									
							number	2,052	
		1LE2321-2CB1					0502-151028		
Restricted						Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-02	en	1/1