Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:				FS: 2	84TS -	p - 25 h	p -												
_							Item-No.					Offer	Offer no.							
Order no.						(Consignment no.						Project							
Remarks																				
Electrical data																				
U Δ/Υ f F [Hz] [H			P [HP]	P [kW]	n [rpm]		1	[Amps]			Nom. Eff Load			[%] Pwr. Factor Lo						
[•]		[112]	[, ,,]	[KVV]	[ibiii]	4/4	3/4	1/2	0	LRC	7/7	317	ZIT		314	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: 284TS Type of constr.:												Motor Prot	.:		NEMA	Des.:	S.F.:	: 1.15		
	Mtr. WT: II			isulation Class.:Standard Class F Insulation					Temp. Rise Cl.: B A								kVA: IP 55			
	IVICI. VVI. II	D3	'	iisulatioii	_1asssta11	uaru Cias	s i ilisulati)II	iise Ci b	e Cl.: B Amb. Temp.: + 40 to -20 °C @10				1000111	KVA. IF 55					
Mecha	anical d	lata																		
Sound	level (SP	L / SWL) a	ıt 60 Hz			d	3(A) / dB	(A)		Thicke	ner									
	`			nd Cente	er Freque			` '		Safe Stall Time Hot						S				
		250	50	0 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S			
S	PL@3							dB(A)			Frame material									
Mome	nt of iner	rtia					Lb-ft²			Color, paint shade Standard Paint - RAL70							L7030			
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epox						oxy (C	2)			
Bearin	gs									Ventil	ation Ty	pe						-		
	g DE ND	DΕ								Method of cooling										
								Ball Bea	ring	Direction of rotation										
	Bearing_Type Ball Bearing AFBMA:								Fan Material											
Grease										VFD CT: VT:										
						07		OZ		Space heaters					-l-					
Capacity oz Grease Type:					02		02	Brake:				- <i>I-</i>								
Grease	турс.									Diake.										
Termi	nal box	[
	Lead Wir	re Connec	tion							Termin	nal box p	osition								
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box										
									Cable	entry					-/-					
Notes:																				
I _A /I _N = lock		rrent / current											eration with r	notor de	sign IC411					
		torque / torqu torque / nomi								2) at rate	d power / at	full load								
Responsible department Technical reference IN LVM					Create SPC	ed by		Approved by				Technical data are subject to chan				ge! There may be discrepancies				
<u> </u>				Docum	ent type					<u> </u>			Document status customer							
Datasheet											Released									
Document title												Document number								
1LE2321-2DB1					31															
												on	Creation date	e	Languag	e Pag	e			
© ABB 2024										01		2024-05-	05 06:38	en	1/1					

			Main ter	minal diagram					
Transmittal, reproduction damages. All rights created	on, dissemination and/or ated by patent grant or re	editing of this document as well as gistration of a utility model or desi	utilization of its contents and cor gn patent are reserved.	nmunication thereof to others wit	hout expres	ss authorization	n are prohibited. Offenders will	be held liable fo	r payment of
Responsible departi	ment	Technical reference	Created by	Approved by	Technica be discre	l data are subj	ect to change! There may en calculated and rating	Link docum	ents
IN LVM				Created automatically	plate val	ues.		© ;;%	
		Document type Wiring diagramm	Document : Released	status					
		Document title		Document	number	200			
		1LE2321-2DB1					0505-063858		oresident.
Restricted © Innomotics 2	2024					Revision AA	Creation date	Language en	Page 1/1