Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor type: FS: 326T - p - 50 hp -  Client order no. Item-No.								Offer no											
Client order no.						terrino.						Onei	Offer no.						
Order no.					(	Consignment no.						Project							
Remarks																			
Electrical data	<u> </u>																		
U D/Y	f	Р	Р	n		I Load	[Amps]				n. Eff Loa			r. Factor Lo		Torque	T <sub>A</sub> /T <sub>N</sub>	T <sub>k</sub> /T <sub>N</sub>	
[V] Δ/1	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
										1									
Frame Type: 326T Type of constr.:				constr.:				Motor Pro				ot.: NEMA D			Des.: S.F.: 1.15		: 1.15		
Mtr. WT: lb	os	lı	Insulation Class.:Standard Class				ion	Temp. R	Temp. Rise Cl.: B Am		Amb. Temp.: + 40 to -20 °C @1000 m			000 m	kVA:		IP 55		
Mechanical d	ata																		
Sound level (SP	L / SWL) a	ıt 60 Hz			dl	B(A) / dE	B(A)		Thicke	ner									
	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A)  Octave Band Center Frequencies Hertz								Safe Stall Time Hot s										
	250				000	4000	8000	Hz	Safe Stall Time Cold s										
SPL@3								dB(A)	Frame material										
Moment of iner	tia					Lb-ft²			Color, paint shade Standard Paint - RAL7030										
Ext Load Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)			
Bearings									Ventilation Type										
Bearing DE   ND	E								Method of cooling										
Bearing_Type							Ball Bea	ring	Direction of rotation										
AFBMA:									Fan Material										
Grease						,			VFD CT: VT:										
Capacity					oz		OZ		Space heaters					-/-					
Grease Type:						'		Brake:							-/-				
Tarresimal have																			
Terminal box																			
Lead Wire Connection								Terminal box position											
Voltage L1 L2 L3 Connected together							ether	Material of terminal box											
									Cable	entry					-/-				
									-										
Notes: I <sub>A</sub> /I <sub>N</sub> = locked rotor cur	ront / current	nominal							2) Valuo i	is valid only	for DOL on	eration with r	motor dos	ian IC411					
M <sub>A</sub> /M <sub>N</sub> = locked rotor t	orque / torqu	ue nominal								d power / at		eration with r	notor des	ign iC411					
M <sub>K</sub> /M <sub>N</sub> = break down t		nal torque	Tachni	cal rafaran		Crost	ad by		LAnne	arad by			Tech	nical data are s	subject to cha	ngel There r	nav he di	iscrenancies	
Responsible depart IN LVM	unent		rechnic	cal referen	ce	SPC	ed by		Appr	oved by			. recn	nical data are s		nge: mere f	nay be als	screpuncies	
<u> </u>			Document type						L			Docu	Document status			custome	r		
Datasheet										Released			1						
Document title 1LE2321-3AB2											Document number			1					
				32															
			1									Revis	ion	Creation date	9	Languag	e Pag	e	
© ABB 2024												01		2024-04-2	27 16:31	en	1/1	<u> </u>	

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	thout express	s authorization	n are prohibited. Offenders will	l be held liable for	r payment of
December 21 to the control of the co		I To the Control of Control	I constitution	I.a	Trackadant	d=4= === ===b		Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by Created automatically	be discrep plate valu	aata are subj oancies betwe ies.	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
		Document type		Created automatically		Document:	status	具織	
Wiring diagramm Released									20.25
		Document title		Document	number				
		1LE2321-3AB2					0427-163123		
Restricted		1			_ L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-04-27	len	1/1