Data sheet for three-phase Squirrel-Cage-Motors ABB																				
					FC 3	267	25.1													
Motor type: FS: 326T - p - 25 hp - Client order no. Item-No.								Offer no.												
Client order no.						terri-No.						Offer	Offer no.							
Order no.						Consignment no.					Proje	Project								
Remarks	Remarks																			
Flectri	cal data																			
Liectii	cai data																			
U		f	Р	Р	n		I Load [Amps]			Non	d [%]	%] Pwr. Factor Loa			Torque	T _A /T _N	T _k /T _N			
[V]	Δ/Υ	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4 1/2		0	LRC			2/4			3/4 2/4		LRT [%]	BDT [%]	
		60	25.00	18.50																
							Ma				tor Prot i			AA Des						
Frame Type: 326T			Type of constr.:						Motor Prot.:					NEMA Des.:			S.F.: 1.15			
	Mtr. WT: lb	S	lı	nsulation (lass.:Stan	dard Clas	ass F Insulation Temp. R			Rise Cl.: B Amb. Temp.: + 40			+ 40 to -20	40 to -20 °C @1000 m k¹			A: IP 55		P 55	
Mecha	anical d	ata																		
	level (SPL		at 60 Hz			Ь	B(A) / dB	(A)		Thicke	ner									
Journa	10001 (51)		Octave Ba	nd Cente	r Freque			(,,)		Safe Stall Time Hot s										
		250				000	4000	8000	Hz	Safe Stall Time Cold					s					
SI	SPL@3 dB(A)								dB(A)	Frame material										
Mome	Moment of inertia Lb-ft ²									Color, paint shade Standard Paint - RAL70						AL7030)			
Ext Loa	id Inertia	Capabili	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (Co							(2)			
Bearin	gs									Ventil	ation Ty	pe								
Bearing	Bearing DE NDE								Method of cooling											
Bearing_Type Ball Bearing								Direction of rotation												
AFBMA:								Fan Material												
Grease							VFD CT: VT:													
Capacity oz oz								Space heaters -/-												
Grease Type:									Brake:											
Termi	nal box																			
	Lead Wire	e Conne	ction							Termir	nal box p	osition								
Voltag	Voltage L1 L2 L3 Connected together							Material of terminal box												
								Cable	entry					-/-						
											-									
										•										
Notes:	ed rotor curr	ent / curren	t nominal							3) Value i	s valid only	for DOL ope	eration with r	notor des	ian IC411					
$M_A/M_N = 10$	ocked rotor to	orque / torq	ue nominal								d power / at									
			iliai torque	Technic	al referen	ce	Creat	ed by		Appr	oved by			Techr	nical data are s	subject to cho	inge! There	may be d	iscrepancies	
IN LVN																				
				Document type						•			Docu	Document status			custom	customer		
Datasheet Datasheet												ased								
Document title 1LE2321-3AD2												Document number Revision Creation date								
)2											11	Language Page				
© ABR	© ABB 2024											01		2024-05-			1/			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or reated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Description		Created automatically	plate valu		ctatus	具織	
Document type Document status Wiring diagramm Released									
		Document title		Document	number				
		1LE2321-3AD2					0502-095903		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-02	en	1/1