Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 3	65T - p	- 75 hp	-											
Client order no.							Item-No.						Offer no.						
Order no.						(Consignment no.						Project						
Remarks																			
<u> </u>	Electrical data																		
Electri	cal data	3																	
U A/Y f P P			11 [1		Nom. Eff Load [%]			14 414 314 314			.		T _k /T _N		
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft] I	_RT [%]	BDT [%]
Frame Type: 365T Type of constr.: NEMA Des										205.4	C F .	1 15							
Frame Type: 365T					Type of constr.:									otor Prot.:					
	Mtr. WT: II	bs	I	nsulation	sulation Class.:Standard Class F Insulati				ulation Temp. Ri			ee Cl.: B Amb. Temp.: + 40 to -20			1000 m	kVA	: IP 55		
Mecha	anical d	lata																	
Sound	Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Thickener																		
	`			ınd Cente	er Freque			` '		Safe Stall Time Hot						S			
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S		
S	PL@3								dB(A)	Frame material									
Mome	Moment of inertia Lb-ft ²								Color,	Color, paint shade Standard Paint - RAL7						L7030			
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)							2)		
Bearin	gs									Ventil	ation Ty	pe							
Bearing	g DE NC	ÞΕ								Method of cooling									
Bearing_Type Ball Beari							ring	Direction of rotation											
AFBM <i>A</i>	۸:									Fan Material									
Grease	2						,	VFD				VFD CT: VT:							
Capacity oz					oz		oz		Space heaters					-/-					
Grease Type:							·		Brake:	Brake:					-/-				
Termi	nal box	[
	Lead Wii	re Connec	tion							Tormir	aal boy n	ocition							
Volta	Voltage L1 L2 L3 Connected together								Terminal box position Material of terminal box										
	g- 2. EZ EZ Connected together								Cable entry										
										Cable	entry					-1-			
										-									
Notes:																			
		rrent / current torque / torqu									s valid only d power / at		eration with r	notor de	sign IC411				
		torque / torqu								∠) at late	a power / dl	. am ioad							
Responsible department Technical reference IN LVM					Created by			Approved by				Technical data are subject to chang				je! There may be discrepancies			
Document type									Document status				custome						
														Released					
Datasheet Document title 1LE2321-3CB2											Document number			1					
				32															
												on	Creation date	9	Language	Page	e		
© ABB 2024										01		2024-05-	07 14:40	en	1/1				

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	r editing of this document as well a egistration of a utility model or des	is utilization of its contents and co	mmunication thereof to others wit	thout expres	s authorizatior	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discrep	data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Document type		Created automatically	plate valu		ctatus	黑微	
	Document type Wiring diagramm Released								
		Document title		Document	number				
		1LE2321-3CB2					0507-144100		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-07	en	1/1