Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:				FS: 3	64TS -	p - 40 h	p -												
							Item-No.					Offer no.								
Order no.						(Consignment no.						Project							
Remarks													1							
Electri	cal data	a																		
U Δ/Υ f P [Hz] [HP]			Р	P [kW]	n [rpm]		1	[Amps]			Nom. Eff Load [%]						Torque	T _A /T _N T _k /T _N		
[1		[112]	[, ,,]	[KVV]	[ibiii]	4/4	3/4	1/2	0	LRC	7/-	317	ZIT	7/-	314	2/4	[lb-ft]	LRT [%]	BDT [%]	
Frame Type: 364TS Type of constr.:											Motor Prot	.:		NEMA	Des.:	S.F.:	: 1.15			
	Mtr. WT: II			nculation (sulation Class.:Standard Class F Insulation				Temp F	Rica Cl · R										
	IVILIT. VVIII	us	'	risulation	Classstall	uaru Cias	s F IIISulatii)	remp. r	Nise Ci.: B	se Cl.: B Amb. Temp.: + 40 to -20 °C @10				1000111	KVA: IP 55			7 33	
Mecha	Mechanical data																			
Sound	level (SP	L / SWL) a	it 60 Hz			d	B(A) / dB	(A)		Thicke	ner									
		C	ctave Ba	nd Cente	er Freque	ncies He	rtz			Safe Stall Time Hot				s						
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold							S			
S	PL@3								dB(A)	Frame	Frame material									
Mome	Moment of inertia Lb-ft ²									Color, paint shade Standard Paint - RAL						L7030				
Ext Loa	ad Inertia	Capabilit	:y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C							2)			
Bearin	gs									Ventil	ation Ty	pe								
Bearing	g DE ND	Œ								Method of cooling										
Bearing	g Type							Ball Bea	ring	Direction of rotation										
	Bearing_Type Ball Bearing AFBMA:								Fan Material											
AFBMA: Grease								VFD CT: VT:												
					oz		OZ		Space heaters				-/-							
Grease Type:									Brake:				-I-							
	<i>3</i> .																			
Termi	nal box																			
Lead Wire Connection Terminal box position																				
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box										
									Cable	entry					-/-					
											,									
Notes:																				
I _A /I _N = lock		rent / current											eration with r	notor de	sign IC411					
		torque / torqu orque / nomi								∠) at rate	d power / at	ruii ioad								
Responsible department Technical reference					Create SPC	d by		Appr	Approved by			Technical data are subject to char				ge! There may be discrepancies				
Document type									Docu	ment st	atus		custome	·r						
Datasheet											Released									
Datasneet Document title 1LE2321-3DC1											Document number									
				1																
												evision Creation date		Languag	e Pag	e				
© ABB 2024										01		2024-05-	03 16:53	en	1/1	l				

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or reated by patent grant or re	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	n are prohibited. Offenders will	be held liable for	r payment of
Responsible depar	rtment	Technical reference	Created by	Approved by	Technical be discre	l data are subj pancies betwe	ect to change! There may een calculated and rating	Link docume	<u>ents</u>
IN LVM		Downsertt	<u> </u>	Created automatically			ctatus		
	Document type Wiring diagramm Released								
		Document title		Document	number	100			
		1LE2321-3DC1					0503-165400		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-03	en	1/1