Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:				FS: 4	05TS -	p - 100 l	ոp -												
Client order no.						I	Item-No.					Offer	Offer no.							
Order no.						(Consignment no.					Proje	Project							
Remarks																				
Electri	cal data	<u> </u>																		
Electri	Cai uata	1																		
U A/Y f P P n				I Load [Amps]				Nom. Eff Load							orque T _A /T _N					
[V]	Δ/1	[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft] I	RT [%]	BDT [%]	
E.		IOETC			T(4.45	
Frame Type: 405TS Type of cons				constr.:			Motor F				Prot.: NEMA D									
	Mtr. WT: lk	os	I	Insulation Class.:Standard Class F Insula					nsulation Temp. Ris			e Cl.: B Amb. Temp.: + 40 to			to -20 °C @1000 m kVA:			: IP 55		
Mecha	Mechanical data																			
Sound	level (SP	I / SWI) a	nt 60 Hz			h	B(A) / dB(A)		Thicke	ner									
Sound level (SPL / SWL) at 60 Hz dB(A) / dB(A) Octave Band Center Frequencies Hertz Safe Stall Time Hot s																				
		250				000	4000	8000	Hz		Safe Stall Time Cold						s			
S	PL@3								dB(A)	Frame material				-						
Mome	Moment of inertia Lb-ft ²								Color, paint shade Standard Paint - RAL7030											
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy (C2)								2)		
Bearin	gs									Ventil	ation Ty	pe								
Bearing	g DE ND	E								Method of cooling										
Bearing	g_Type						Ball Bearing Direction of rotation				ation									
AFBM <i>A</i>	۸:									Fan Material										
Grease	e										VFD CT: VT:									
Capacity oz					oz		oz	Space heaters -/-												
Grease Type:					E				Brake: -/-											
Termi	nal box																			
	Lead Wire Connection							Termi	Terminal box position											
Volta	Voltage L1 L2 L3 Connected together							ether	Material of terminal box											
									Cable entry -/-											
										_										
Notes:																				
		rent / current torque / torqu									s valid only d power / at		eration with n	notor de	sign IC411					
		orque / torqu orque / nomi								<i>∠)</i> at late	a power / dl	. an ioad								
Responsible department Technical reference					Created by			Appr	Approved by			Technical data are subject to chan			nge! There n	ay be dis	screpancies			
IN LVI	Л							SPC						<u> </u>			customer			
Document type													Document status							
Datasheet Document title 1LE2321-4BA2											Released									
								Docum			ument number									
				∠						Rovic:	Revision Creation date			Language	Language Page					
© ABB 2024												01		2024-04-2			1/1			

			Main te	rminal diagram					
Transmittal, reproduc	tion, dissemination and/or	editing of this document as well a egistration of a utility model or des	s utilization of its contents and co	mmunication thereof to others wit	ithout express	s authorization	n are prohibited. Offenders will	l be held liable fo	r payment of
damages. All rights cr	eated by patent grant or re	egistration of a utility model or des	ign patent are reserved.						
Responsible depar	tment	Technical reference	Created by	Approved by	Technical be discren	data are subj	iect to change! There may een calculated and rating	Link docume	ents
IN LVM			<u> </u>	Created automatically	plate valu	es.		回兴趣	東京公司
	Document type Document status							7	
		Wiring diagramm	Released						
		Document title 1LE2321-4BA2				Document	number 0427-222536		
Restricted					L	Revision	Creation date	Language	Page
© Innomotics	2024				- 1	AA	2024-04-27	en	1/1