Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 4	49TS -	p - 250	hp -											
							Item-No.						Offer no.						
Order no.						(Consignme	nt no.					Project						
Remarks													1						
Electri	Electrical data																		
U Δ/Υ f [Hz] [H			P [HP]	P [kW]	n [rpm]	414	1	[Amps]		1.00	Nom. Eff Load [%]							T _A /T _N T _k /T _N	
[*]		[112]	[]	[KVV]	[ibiii]	4/4	3/4	1/2	0	LRC	17 1	3/ 1	2/1		7 3/1	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 449TS Type of constr.:										Motor Prot	.:		NEMA	Des.:	S.F.:	: 1.15			
				2.					Temp F	o. Rise Cl.: B Amb. Ten									
Mtr. WT: lbs Insulation Class.:Standard C				uaru Cias:	s F IIISuldu	ווכ	use CI.: B	se Cl.: B Amb. Temp.: + 40 to -20 °C @1000 n				1000 111	KVF	kVA: IP 55					
Mech	anical d	lata																	
Sound	level (SP	L / SWL) a	it 60 Hz			dl	B(A) / dB((A)		Thicke	ner								
		C	ctave Ba	nd Cente	er Freque	ncies He	rtz			Safe Stall Time Hot s									
		250	50	0 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold					S				
S	PL@3								dB(A)	Frame material									
Mome	nt of iner	rtia					Lb-ft²			Color, paint shade Standard Paint						Paint - RA	nt - RAL7030		
Ext Loa	ad Inertia	Capabilit	:y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy						oxy (C	2)		
Bearin	gs									Ventilation Type									
Bearin	g DE ND	DΕ								Method of cooling									
Bearing	g Type							Ball Bea	ring	Direction of rotation									
AFBM <i>A</i>								J	Fan Material										
Grease							ļ			VFD			CT: VT:						
					oz		oz		Space heaters						-l-				
Grease Type:					02		02	Brake:					-l-						
	31																		
Termi	nal box	[
Lead Wire Connection Terminal box position																			
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box									
										Cable entry -/-									
Notes:																			
$M_A/M_N = I$	ocked rotor	rrent / current torque / torqu	ue nominal								s valid only d power / at		eration with r	notor de	esign IC411				
1 · · · · · ·						Create SPC	Created by			Approved by			Technical data are subject to char				nge! There may be discrepancies		
					Document type						D			Document status				r	
Datasheet												Released				custome			
Document title 1LE2321-4DA5											Document number								
				۸5	····														
													Revision Creation date		Languag	e Pag	e		
© ABB 2024										01		2024-04-	30 20:49	en	1/1				

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout express a	uthorization	are prohibited. Offenders will	l be held liable fo	r payment of
December 21 to the control of the co		I To the Control of Control	I constitution	I	T +		and the second of the second	Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by	be discrepan	ita are subj icies betwe	ect to change! There may en calculated and rating	Link docum	<u>ents</u>
		Document type		Created automatically	Documer		status	黑鹟	
	Wiring diagramm Released								20.25
Document title Docume							number	¥2.	
		1LE2321-4DA5					0430-204940		
Restricted		1				evision	Creation date	Language	Page
© Innomotics	2024				lΑ	Α	2024-04-30	len	1/1