Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 3	64T - p	- 30 hp	_											
							Item-No.					Offer	Offer no.						
Order no.							Consignme	nt no.					Project						
order no.							.011319111110						Project						
Remarks																			
Electri	cal data	a																	
U A/Y f P P			Р	n		I Load [Amps]				Nom. Eff Load [%]						.		T <sub>k</sub> /T <sub>N</sub>	
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 364T Type of constr.:					constr.:				Motor P			Motor Prot	Prot.: NEMA [			Des.:	Des.: S.F.: 1.15		
Mtr. WT: lbs			ı	Insulation Class.:Standard Class F Insulation					Temp. Rise Cl.: B Amb. Ter			ıb. Temp.:	+ 40 to -20	) ℃ @	1000 m	kV/	kVA: IP 55		55
Mech	Mechanical data																		
Sound	level (SP	PL / SWL) a	ıt 60 Hz			d	3(A) / dB	(A)		Thicke	ner								
Souria	10001 (31			nd Cente	er Freque					Safe Stall Time Hot s									
		250				000	4000	8000	Hz	Safe Stall Time Cold						s			
S	PL@3								dB(A)	Frame material				5					
Mome	nt of ine	rtia					Lb-ft²			Color, paint shade Standard Paint						Paint - RA	: - RAL7030		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy						oxy (C	2)		
Bearin	gs									Ventilation Type									
Bearing	g DE   NC	DE								Method of cooling									
Bearing	g_Type							Ball Bearing			Direction of rotation								
AFBM <i>A</i>	۸:									Fan Material									
Grease	•									VFD CT: VT:									
Capacity oz					OZ		oz	Space heaters				-/-							
Grease Type:								Brake:					-/-						
Termi	nal box																		
	Lead Wire Connection								Terminal box position										
Volta	Voltage L1 L2 L3 Connected together								ether	Material of terminal box									
										Cable	entry					-/-			
										-									
Notes: I <sub>A</sub> /I <sub>N</sub> = lock	ked rotor cur	rrent / current	nominal							3) Value i	s valid only	for DOL op	eration with r	notor de	sign IC411				
		torque / torqu torque / nomi								2) at rate	d power / at	full load							
Responsible department Technical reference IN LVM					ce	Create SPC	ed by		Appr	Approved by			Technical data are subject to char				nge! There may be discrepancies		
Document type													Document status Released				r		
Datasheet  Document title  1LE2421-3CD1																			
										Document number				1					
				)1															
												Revisi	on	Creation date		Languag			
© ARF	3 2024												01		2024-04-	Z8 12:23	en	1/1	l

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	ithout express a	uthorization	are prohibited. Offenders will	l be held liable fo	r payment of
December 21 to the control of the co		I To the Control of Control	I constitute	I	T = -111			Treat access	
Responsible depar	ument	Technical reference	Created by	Approved by Created automatically	be discrepai plate values	aca are subj ncies betwe i.	ect to change! There may en calculated and rating	Link docum	ents
		Document type	<u> </u>	Created automatically	Document		status		
	Wiring diagramm Released  Document title Document number								20.25
		1LE2421-3CD1					0428-122318		
Restricted		1				evision	Creation date	Language	Page
© Innomotics	2024				I <sub>A</sub>	A	2024-04-28	len	1/1