Data sheet for three-phase Squirrel-Cage-Motors ABB																			
Motor	type:				FS: 3	64TS -	p - 60 h	p -											
Client order no.							Item-No.						Offer no.						
Order no.						(Consignment no.						Project						
Remarks													_1						
Electrical data																			
U Δ/Υ f P [Hz] [HP]			P [kW]	FLAME F 3			[Amps]	-		Nom. Eff Load [%] Pwr. Factor Load [%] 2/4 4/4 3/4 2/4				T _A /T _N	T _k /T _N	
[v]		[П2]	[HF]	[KVV]	[thiii]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	+ 3/4	2/4	[lb-ft]	LRT [%]	BDT [%]
Frame Type: 364TS Type of constr.:											Motor Prot			NEMA	Des :	S E	: 1.15		
								T [1000						
	Mtr. WT: II	DS		nsulation	ulation Class.:Standard Class F Insulation				Temp. Rise Cl.: B Amb. Ten			ib. Temp.:	+ 40 to -20	J ~ (@	1000 m	kVA	kVA: IP 55		' 55
Mecha	anical d	lata																	
Sound	level (SP	L / SWL) a	nt 60 Hz			d	B(A) / dB	(A)		Thicke	ner								
Journa	10 (01			nd Cente	r Freque			.,,		Safe Stall Time Hot s									
		250				000	4000	8000	Hz	Safe Stall Time Cold						S			
S	PL@3								dB(A)	Frame material				5					
Mome	nt of iner	rtia					Lb-ft²			Color, paint shade Standard Pain						Paint - RA	int - RAL7030		
Ext Loa	ad Inertia	Capabilit	ty:				Lb ft²			Coating (paint finish) Standard Alkyed + Epoxy							оху (С	2)	
Bearin	ıgs									Ventilation Type									
	g DE ND)E								Method of cooling									
	•							Ball Bearing			Direction of rotation								
Bearing_Type Ball Beari							J	Fan M											
Grease								VFD					CT: VT:						
					OZ		oz		Space heaters				-l-						
Grease Type:								Brake:					-/-						
	<i>3</i> .																		
Termi	nal box	[
	Lead Wir	re Connec	ction							Termir	nal box p	osition							
Volta	Voltage L1 L2 L3 Connected together								ether	Terminal box position Material of terminal box									
	g- 2. L2 L5 Connected together									Cable entry -/-									
										Cable	entry					-/-			
										-									
Notes:		rrent / curren	t nominal							3) Value i	s valid only	for DOL on	eration with r	motor do	esian IC411				
$M_A/M_N = 1$	ocked rotor	torque / torqu	ue nominal								d power / at		eracion with	notor de	-sigir iC+11				
M _e /M _N = break down torque / nominal torque Responsible department IN LVM					ce	Create	ed by		Approved by				Technical data are subject to chan				ge! There may be discrepancies		
Document type					1	1510						Document status customer				r			
Datasheet Document title 1LE2421-3DB1												Released Document number							
				31															
											Revisi	ion	Creation dat	е	Languag	e Pag	e		
© ABB 2024										01		2024-05-	06 19:44	en	1/1	l			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	s utilization of its contents and co ign patent are reserved.	mmunication thereof to others wit	ithout expres	s authorizatior	n are prohibited. Offenders will	l be held liable fo	r payment of
D 'I I I		I To the Control of Control	I constitution	I.a	T	-d-4		Treatment	
Responsible depar	tment	Technical reference	Created by	Approved by	be discrep	aata are subj oancies betwe ies.	iect to change! There may een calculated and rating	Link docum	<u>ents</u>
		Document type	1	Created automatically		Document :	status		
Wiring diagramm Released								200	20.25
		Document	number						
		1LE2421-3DB1			1		0506-194452		
Restricted		1			L	Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-06	len	1/1