Data sheet for three-phase Squirrel-Cage-Motors ABB																				
Motor	type:				FS: 4	05T - p	- 75 hp	-												
Client order no.						I	Item-No.						Offer no.							
Order no.						(	Consignment no.						Project							
Remarks																				
	Electrical data																			
Electri	cal data	a																		
U A/Y f P P n				I Load [Amps]				Nom. Eff Load			l .	r. Factor Lo	214	Torque T <sub>A</sub> /T		T <sub>k</sub> /T <sub>N</sub>				
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
Fra	ma Tunas	40ET			Tuno of	constr.							Motor Prot			NEMA	D :	C.F.	. 1 15	
Frame Type: 405T				Type of constr.:												MA Des.: S.F.: 1.15				
	Mtr. WT: lbs In			nsulation	sulation Class.:Standard Class F Insulation				Temp. Rise Cl.: B			Amb. Temp.: + 40 to -20 °C @1000 m				kVA: IP 55			55	
Mecha	Mechanical data																			
Sound	level (SP	PL / SWL) a	it 60 Hz			d	B(A) / dB	(A)		Thicke	ner									
	`			ınd Cente	er Freque			. ,		Safe S						S				
		250	50	00 10	000 2	000	4000	8000	Hz	Safe Stall Time Cold						S				
S	PL@3								dB(A)	Frame material										
Mome	nt of ine	rtia					Lb-ft²			Color,	Color, paint shade Standard Pain						Paint - RA	int - RAL7030		
Ext Loa	ad Inertia	Capabilit	y:				Lb ft²			Coatin	Coating (paint finish) Standard Alkyed + Epoxy (							oxy (C	2)	
Bearin	gs									Ventilation Type										
Bearing	g DE   NC	DE								Method of cooling										
Bearing	g_Type							Ball Bearing			Direction of rotation									
AFBM <i>A</i>	۸:									Fan Material										
Grease	•						'			VFD CT: VT:										
Capacity oz					oz		oz		Space heaters						-/-					
Grease Type:								Brake:	Brake:					- -						
Termi	nal box	<u> </u>																		
			tion																	
	Voltage L1 L2 L3 Connected together								ether	Terminal box position  Material of terminal box										
Voita	Voltage L1 L2 L3 Connected together								ctrici	Cable entry -/-										
									Cable	entry					-1-					
										-										
Notes:	ced rotor cur	rrent / current	nominal							3) Value i	s valid only	for DOL on	eration with r	notor de	sian IC411					
$M_A/M_N = 1$	ocked rotor	torque / torqu	ue nominal								d power / at			ilotoi ac	sign ic i i i					
M <sub>s</sub> /M <sub>N</sub> = break down torque / nominal torque  Responsible department Technical reference Created by						ed by		Approved by				Technical data are subject to change! There may be discrepa					screpancies			
IN LVM				Document type							10.			Document status custom						
														Document status				r		
Datasheet  Document title  1LE2421-4AC2											Released  Document number									
				~? -								Document number								
				12 1 - 7/\(	CZ								vision Creation date		Languag	Language Page				
© ABB 2024												01		2024-05-			1/1			

			Main te	rminal diagram					
Transmittal, reproduc damages. All rights cr	tion, dissemination and/or eated by patent grant or re	rediting of this document as well a egistration of a utility model or des	is utilization of its contents and co sign patent are reserved.	mmunication thereof to others wit	thout expres	s authorization	n are prohibited. Offenders will	l be held liable fo	r payment of
December 21 to the control of the co		I To the Control of Control	I constitution	I	T	I data ana anti		Treatment	
Responsible depar	ument	Technical reference	Created by	Approved by Created automatically	be discre plate valu	uata are subj pancies betwe ues.	ect to change! There may een calculated and rating	Link docume	ents
		Document type	<u> </u>	Created automatically	1	Document	status		
Wiring diagramm Released								300	20.25
	Document	number							
		1LE2421-4AC2				WDS-240	0507-033930		
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					AA	2024-05-07	len	1/1