<u>Data</u>	sheet	for th	nree-p	hase S	Squirre	el-Ca	ige-Mo	tors A	<u>BB</u>											
Motor	type:				FS: B	447T	- p - 150	hp -												
Client order no.						Item-No.					Offer	Offer no.								
Order no.						Consignment no.					Proje	Project								
Remarks																				
Electri	cal data	1																		
U	Δ/Υ	f	Р	Р	n		I Load [Amps]				Nom. Eff Load [%]							Torque T <sub>A</sub> /T <sub>N</sub>		
[V]		[Hz]	[HP]	[kW]	[rpm]	4/4	3/4	1/2	0	LRC	4/4	3/4	2/4	4/4	3/4	2/4	[lb-ft]	LRT [%]	BDT [%]	
		60	150.00	110.00																
Frar	ne Type: B	447T			Type of	constr.	:		Motor Pro				ot.: NEM			A Des.: S.F.: 1.15				
1	Mtr. WT: lb	15	Ir	nsulation (	lass.:Stan	dard Cla	ass F Insulation Temp. Rise Cl.				e Cl.: B Amb. Temp.: + 40 to -20 °C				C @1000 m kVA: IP 5				P 55	
Mecha	anical d	ata																		
										Thisles										
Sound	level (SPI		Octave Ba	nd Cente	r Freque		dB(A) / dB	(A)		Thicke		Hot					s			
		25				000	4000	8000	Hz	Safe Stall Time Hot Safe Stall Time Cold							s			
SI	PL@3							dB(A) Frame material						5						
Momer	nt of iner	tia					Lb-ft²			-	Color, paint shade Standard Paint - RA						RAL7030	)		
Ext Loa	ıd Inertia	Capabili	ty:				Lb ft <sup>2</sup>			Coating (paint finish) Standard Alkyed + Epoxy						Epoxy (C	2)			
Bearin	gs									Ventil	ation Ty	pe								
Bearing	g DE   ND	E								Method of cooling										
Bearing_Type Ball Bearing							ring	Direction of rotation												
									Fan M	Fan Material										
Grease								VFD CT: VT:												
Capacit	-					οz		oz		Space heaters				-1-						
Grease Type:						Brake:										-1-				
Termi	nal box																			
	Lead Wir	e Conne	ction							Termir	nal box po	osition								
Voltage L1 L2 L3 Connected together							al of tern		ŕ											
							Cable			-			-/-							
											2									
										-										
Notes:	ed rotor cur	rent / curren	t nominal							3) Value i	s valid only	for DOL ope	eration with r	notor desig	n IC411					
	ocked rotor t										d power / at f									
M <sub>K</sub> /M <sub>n</sub> = break down torque / nominal torque Responsible department Technical reference Created by							Approved by			Technical data are subject to change! There may be discrepancies										
· ·	N LVM SPC																			
Document type							I			Document status				custon	her					
Datasheet Document title 1LE2421-4EC3										Released				4						
												Document number								
										Revis	on C	reation date	<u>م</u>	Langua	age Pa	ne				
© ABB 2024										01			- 01 04:35	-	1/					

			Main ter	minal diagram					
								]	
Transmittal, reproduct damages. All rights cre	ion, dissemination and/or ated by patent grant or re	editing of this document as well as gistration of a utility model or desig	utilization of its contents and cor gn patent are reserved.	mmunication thereof to others wit	hout expre	ss authorization	are prohibited. Offenders will	l be held liable f	or payment of
Posponsible data	mont	Technical reference	Created by	Approved by	Technic	l data are sub-	ect to change! There may	Link de ev	onto
Responsible depar IN LVM	ment	recrimical reference	Created by	Approved by Created automatically	lechnica be discre plate val	n aata are subj epancies betwe lues.	ect to change! There may en calculated and rating	Link docum	
		Document type		c.cutcu uutomatically		Document s	status	見認	
	Document type         Document status           Wiring diagramm         Released           Document title         Document number								
		1LE2421-4EC3		WDS-240					
Restricted		1				Revision	Creation date	Language	Page
© Innomotics	2024					АА	2024-05-01	en	1/1
		•				•		•	-